

2018 USRA B-MOD RULES

Published November 13, 2017
Amended July 16, 2018



THE RULES AND/OR REGULATIONS SET FORTH HEREIN ARE DESIGNED TO PROVIDE FOR THE ORDERLY CONDUCT OF RACING EVENTS AND TO ESTABLISH MINIMUM ACCEPTABLE REQUIREMENTS FOR SUCH EVENTS. THESE RULES SHALL GOVERN THE CONDITION OF SPEEDWAY EVENTS AND, BY PARTICIPATING IN THESE EVENTS, ALL RACEWAY COMPETITORS ARE DEEMED TO HAVE COMPLIED WITH THESE RULES. NO EXPRESS OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM PUBLICATION OF, OR COMPLIANCE WITH THESE RULES AND REGULATIONS. THEY ARE INTENDED AS A GUIDE FOR THE CONDUCT OF THE SPORT AND IN NO WAY ARE A GUARANTEE AGAINST INJURY OR DEATH TO PARTICIPANTS, SPECTATORS OR OTHERS.

Changes from the 2017 USRA B-Mod rules and/or new additions are **highlighted in red**. Changes made for grammatical purposes or to improve clarity are not highlighted.

References are made throughout these regulations requiring and/or recommending that particular products meet certain specifications. These products are manufactured to meet or exceed certain criteria and are labeled as such upon satisfying those criteria. Any change to these products voids that certification. Under no circumstances may any certified product be altered from the "as manufactured" condition or such certification is voided.

The United States Racing Association shall hereafter be simply referred to as the USRA throughout the rules description. USRA official(s) shall include all personnel employed as an official by participating racetrack.

TABLE OF CONTENTS

- Article 1: Definitions
- Article 2: General Rules
- Article 3: Points System
- Article 4: Body
- Article 5: Roll Cages
- Article 6: Frame
- Article 7: Cockpit, Steering & Seat
- Article 8: Suspension
- Article 9: Electrical System
- Article 10: Fuel System
- Article 11: Tires & Wheels
- Article 12: Braking System
- Article 13: Drive Shaft
- Article 14: Transmission
- Article 15: Rear End
- Article 16: Engine
- Article 17: Weight
- Article 18: Safety
- Article 19: Claiming Procedures
- Amendments

ARTICLE 1: DEFINITIONS

- 1.1 **Racecar:** An automobile designed solely for competition on oval race tracks, controlled from within by a driver.
- 1.2 **Automobile:** A vehicle which carries its own motor and operates on four non-aligned complete wheels, of which two are used for steering and two for propulsion.
- 1.3 **Vehicle:** A man-made locomotive device propelled by constantly taking real support on the earth's surface whereas the propulsion and steering are under the control of a driver aboard the vehicle.
- 1.4 **Driver:** The person controlling the operation of the racecar. The driver is expected to understand how to operate the mechanisms which control the speed, direction and braking of the racecar.

- 1.5 **Participant:** A person directly involved in the mechanical operation and/or management of a racecar, including, but not limited to, drivers, crew members, racecar owners, sponsors and their family members.
- 1.6 **Event:** A USRA-sanctioned competition between two or more drivers and their racecars. An event shall consist of practice (hot laps) and actual racing contests.
- 1.7 **Official:** An official shall be any person participating in the exercise of authority for enforcing or interpreting these rules. The official may also make judgments concerning the conduct of participants and declare penalties for breaches of these rules, as well as perform technical inspections on any racecar. The combination of officials may vary from week to week and from one racetrack to another.
- 1.8 **Promoter:** An entrepreneur who oversees the operations of the racetrack, either as a tenant or owner of the facility. Furthermore, the promoter is the person responsible for the implementation of rules, hiring staff and financial compensation to participants.
- 1.9 **Cockpit:** The volume of the racecar which accommodates the driver.
- 1.10 **OEM:** An original equipment manufacturer (OEM) manufactures products or components that are purchased by another company and retailed under that purchasing company's brand name. OEM refers to the company that originally manufactured the product. OEM replacement parts are those which have been manufactured by another company to the same specifications as the OEM parts.
- 1.11 **EIRI:** Except in rare instances.

ARTICLE 2: GENERAL RULES

- 2.1 USRA rules shall apply at all events. All participants are subject to the rules of the USRA and are expected to know the rules. **These rules are a guideline as to what is permitted and/or not allowed. If these rules do not explicitly say it is permitted, then you must contact the USRA to identify if the part in question is permitted for competition.** An expressed ignorance of USRA rules by any participant will not be recognized as a valid argument for failure to comply with USRA rules. Some tracks may have amendments, additions or other adjustments to the rules for a particular class. Promoters must make these differences clear, in writing, posted online and available to drivers at all times. Drivers should verify rules packages with sanctioned track prior to competing at an unfamiliar venue.
- 2.2 Approval of any racecar by an official shall mean that the racecar is approved for participation in the event and shall not be construed in any way to mean that the inspected vehicle is guaranteed to be mechanically sound or safe. Be it further declared that officials and/or the USRA shall not be liable for any mechanical failure, nor for any losses, injuries or death resulting from the same.
- 2.3 Conduct:**
- 2.3.1 Participants will conduct themselves as professionals. Any unsportsmanlike conduct by a participant shall be grounds for disqualification and/or punitive action by the USRA. This will be strictly enforced.
- 2.3.2 Drivers are responsible for the conduct and actions of their car owners, crew members, sponsors and family members.
- 2.3.3 Absolutely no alcoholic beverage or other illegal chemical substance may be consumed by a driver prior to, or during, an event. The duration of the event shall also include all support class events run as a part of the overall program. The use, sale or distribution of illegal drugs at any time shall be cause for immediate and indefinite suspension.
- 2.3.4 Any participant who defies or violates the intent or spirit of the USRA rules shall be considered to have engaged in unsportsmanlike conduct and shall be dealt with accordingly and swiftly by the USRA.
- 2.4 All drivers must be at least fourteen (14) years of age (proof of age required). Drivers under eighteen (18) years of age are required to have a signed and notarized Parental Consent Form. The Parental Consent Form must be signed by a parent or legal guardian, and must be received by USRA headquarters prior to participation of the driver in any event.
- 2.5 The USRA may require any driver to undergo a physical examination by a licensed health care provider prior to being allowed to participate in any event.
- 2.6 No equipment or racecar will be considered as having been approved by reason of having passed through inspection unobserved.
- 2.7 All racecars must be able to join the race lineup on demand and unassisted, or must go to the rear of the lineup for the start of the race.
- 2.8 The USRA reserves the right to add to, delete, supersede or modify any rule, exhibit or drawing that the USRA deems necessary for the conduct of events and/or safety of participants. All amendments are effective on the date of publication by the USRA regardless of when a person subject to the rules receives actual notice of the amendment.

- 2.9 Every driver must inspect the racing surface and the track area to learn of any obstructions or other defects which, in the driver's opinion, presents an unsafe condition for competition. The driver shall report any unsafe condition in writing to an official. Any driver that competes in an event is considered to have inspected the track surface and surrounding perimeter to determine that all conditions are satisfactory. If the driver does not feel that the conditions are satisfactory, the driver should not compete in the event. The driver further acknowledges that he or she is aware that auto racing involves risk, and that by competing in an event, the driver assumes these risks with full awareness and responsibility.
- 2.10 All drivers are responsible for registering their racecar for each event in order to ensure their respective starting position in each event.
- 2.11 The USRA and/or promoter reserve the right to refuse to accept the entry of any racecar or participant. Furthermore, the USRA and/or promoter reserves the right to revoke or cancel any entry, or any participant's claimed right to be on the racetrack's premises, if it is determined that a participant's presence or conduct is not in the best interest of the sport of auto racing, other participants, spectators, track management and/or employees of the USRA.
- 2.12 Lighted signaling devices, hand signals or any other equipment or methods used for communication during an event between a non-competing participant and a driver is not allowed.
- 2.13 Radios and any other devices used for transmitting or listening are not allowed on the racecar. Exception: Officials may require drivers to utilize a one-way radio with no scanning capabilities to enable audio communication from officials to drivers only. Furthermore, racecars may be fitted with a timing transponder as supplied by officials.
- 2.14 No computers allowed on the racecar, including, but not limited to, electronic traction control devices. Any driver found to be using traction control will be subject to a minimum fine of five thousand dollars (\$5,000) and up to a lifetime suspension from all events.

2.15 Technical Inspections:

- 2.15.1 For all classes at all events, the top four (4) finishers in the main event and any other racecars as instructed by officials, will be required to report to a designated area after the completion of the main event where mandatory and varied post-race technical inspections will be required to take place.
- 2.15.2 Each racetrack is required to have a USRA-certified technical inspector at each event.
- 2.15.3 At the discretion of the official(s) overseeing an event, any participant may be disqualified by the official(s) for violation of any USRA rule and/or equipment or action(s) deemed to be hazardous to other participants or officials.
- 2.15.4 All racecars are subject to inspection by an official at any time. Any driver whom refuses to allow any inspection by an official, or terminates an inspection in progress, shall be subject to a fine of two thousand dollars (\$2,000), suspension from all events for fourteen (14) days, loss of all points (national and track) earned to-date for the current season and forfeiture of all cash and/or awards earned at the event.
- 2.15.5 Any illegal part discovered through inspection any time after the driver signs in to compete in that event can be confiscated by an official and forfeited by the driver. For first infraction, driver discovered to be using illegal parts of any kind shall be subject to a fine of up to two thousand dollars (\$2,000), suspension from all events for up to fourteen (14) days, possible loss of all points (national and track) earned to date for the current season and forfeiture of all cash and/or awards earned at the event. For second infraction, driver shall be subject to a fine of up to five thousand dollars (\$5,000), suspension from all events for up to one (1) year, loss of all points (national and track) earned to date for the current season and forfeiture of all cash and/or awards earned at the event. Confiscated parts will be sent to manufacturer for inspection. Failure by the driver to surrender any illegal part for confiscation shall result in a separate penalty, in addition to other applicable penalties under this rule.
- 2.15.6 All measurements must be made while the racecar is stationary on a flat horizontal surface.
- 2.16 **Decals and Contingency Awards:**
- 2.16.1 Approved USRA sponsor decals must be displayed in required locations on the racecar in order for the driver to participate in any prize money, points funds and/or contingency awards which require specific decals and/or decal placement for eligibility. All decals shall be distributed by the USRA or racetrack, along with a description of each sponsor's program, decal placement requirements and sponsor's contact information.
- 2.16.2 Each racecar must properly display the approved USRA logo decal or USRA Weekly Racing Series decal in order to participate in any points funds. Decal must be positioned on both sides of the racecar at the front of the door below the window opening.

2.17 Licenses and Points Funds:

- 2.17.1 All drivers competing in USRA-sanctioned events must possess a valid USRA license.
- 2.17.2 Drivers may purchase a USRA Temporary License for \$10 which is valid for one (1) event only. Drivers opting for a Temporary License will earn one-half of the published points funds distributed by the USRA. The purchase price of a Temporary License will not apply toward the cost of purchasing a USRA Competitor License if the driver opts to purchase one later.
- 2.17.3 To be eligible for national points funds, driver must have competed in a minimum of fifty percent (50%) of the events held at any one of the USRA-sanctioned tracks at which that driver competed with a USRA Competitor License (minimum of 8 events with a minimum of 4 starts). To be eligible for track points funds, driver must have competed in a minimum of fifty percent (50%) of the events held at the USRA-sanctioned track for which the points funds are being awarded.
- 2.18 Decisions of the USRA are final and binding without exception.
- 2.19 These rules have been set by the USRA and are subject to change without notice. All promoters will be informed of any changes to these rules after the date of publication, and those changes should be made available to drivers at each racetrack and/or announced at drivers meeting. The USRA will publish amendments to these rules on the USRA website.

ARTICLE 3: POINTS SYSTEM

- 3.1 Drivers competing in a USRA-sanctioned event are eligible to earn national, regional and track points at the racetrack where the points were earned for that class. Points are awarded to the driver only (no driver substitutions). A driver may register a one-time-only "provisional" start by paying a \$50 fee to the racetrack prior to the event. Upon receipt of the fee, driver will receive credit for attendance and earn the minimum track, regional and national points for starting.
- 3.2 Points will only be awarded to drivers at events held and officially reported to the USRA by the promoter. Promoter is solely responsible for gathering and submitting complete event results in a timely manner.
- 3.3 Track Points**
 - 3.3.1 Track points will be awarded from **March 1 through September 3, 2018.**
 - 3.3.2 At the discretion of the promoter, track points may include all events held at that track or only those they designate as such. A track may award national points but not track points at any given event.
 - 3.3.3 Track points will be awarded to each driver in the main event as follows: 1st - 100 points, 2nd - 95 points, 3rd - 91 points, 4th - 87 points, 5th - 84 points, 6th - 81 points, 7th - 78 points, 8th - 76 points, 9th - 74 points, 10th - 72 points, 11th - 70 points, 12th - 68 points, 13th - 66 points, 14th - 64 points, 15th - 62 points, 16th - 60 points, 17th - 58 points, 18th - 56 points, 19th - 55 points, 20th - 54 points, 21st - 53 points, 22nd - 52 points, 23rd - 51 points. All other drivers that start the main event and finish below 23rd are awarded 50 points. All drivers that fail to start or qualify for the main event are awarded 45 points
- 3.4 Regional Points**
 - 3.4.1 Regional points will be awarded from **March 1 through September 3, 2018.**
 - 3.4.2 Regional points will be the total of all track points earned by a driver at one or more tracks in a particular region.
- 3.5 National Points**
 - 3.5.1 National points will be awarded to each driver based on his/her best twenty (20) points nights in class from **January 1, 2018, through September 30, 2018, plus three additional USRA Nationals events to be held at three tracks to be determined during the month of October.**
 - 3.5.2 National points will be awarded to each driver in the main event as follows: 1st - 200 points, 2nd - 190 points, 3rd - 182 points, 4th - 174 points, 5th - 168 points, 6th - 162 points, 7th - 156 points, 8th - 152 points, 9th - 148 points, 10th - 144 points, 11th - 140 points, 12th - 136 points, 13th - 132 points, 14th - 128 points, 15th - 124 points, 16th - 120 points, 17th - 116 points, 18th - 112 points, 19th - 110 points, 20th - 108 points, 21st - 106 points, 22nd - 104 points, 23rd - 102 points. All other drivers that start the main event and finish below 23rd are awarded 100 points. All drivers that fail to start or qualify for the main event are awarded 90 points.
 - 3.5.3 One (1) bonus point is awarded to each driver for each position advanced in the main event from the actual starting position to the official finishing position. Example: start 10th, finish 2nd = 8 bonus points. Bonus points equivalent to the total number of drivers in class will also be awarded to each driver in each class, with a maximum of 24 bonus points awarded to each driver.

- 3.5.4 The three USRA Nationals events in October will award a true car count bonus with no maximum on bonus points awarded for car count. A driver may compete in one, two or all three USRA Nationals events, but national points will only be awarded to that driver for the event in which he/she recorded his/her best total points effort.
- 3.5.5 In the event of a tie for first place in the final national and/or track points, the champion shall be the driver with the most wins. Should a tie still exist after wins are counted, the next determining factor(s) shall be top-5 finishes, and then top-10 finishes, and then total number of events, and then the highest finisher in the most recent event(s) until the tie is broken. Drivers that are tied in all other positions shall remain tied. Points funds, if any, for positions that are tied shall be divided evenly between the drivers that are tied.

ARTICLE 4: BODY

- 4.1 1970 or newer American compact passenger cars only (panel vans and/or station wagons are not allowed). Plastic and/or composite body panels are not allowed.
- 4.2 An aluminum half-windshield may be used on driver's side of the front window opening only.
- 4.3 Stock appearing front window support units must be used (painted roll bars are not acceptable substitutes). Front window may have a support of no more than twenty (20) inches at bottom, going straight up to top.
- 4.4 A minimum window opening of twelve (12) inches must be maintained on all four window openings (front, back, left and right).
- 4.5 Streamlining at top of windshield is not allowed. Bodies must have standard appearing windshield opening and corner post must follow standard configuration.
- 4.6 Original roof line of vehicle must be maintained with a maximum of five (5) inches of slope from rear to front. No more than one-half (0.5) inch stiffener allowed at the rear of the roof and must turn down perpendicular to the ground. A maximum of one inch roof lips allowed on outside edge of roof. A maximum of four inch sides on roof allowed. OEM Gremlin roofs are not allowed. Fiberglass roofs are permitted. Aluminum roofs are permitted but must remain flat and not concaved.
- 4.7 Sail panels must be solid and of matching design with matching styles on both sides of racecar. Sail panel may be no farther forward than the driver's seat and no farther back than rear of decking. **Sail panel must be mounted within one (1) inch of the outer edge of deck and flush with the outer edge of roof.**
- 4.8 Sail panels may have no more than four (4) inch bow from top to bottom. A maximum eighteen (18) inches of sail panel along the roof and maximum five (5) inches tall at rear of decking and must be a straight line from back edge of roof to back edge of deck when the sail panel is held flat. Leading edge must within two inches of 90 degrees from roof to quarter panel.
- 4.9 Hood may be no more than two (2) inches above decking and must be sealed off from driver. Reverse hood rake is not allowed. Hood must be level or slope forward toward nose of racecar. A maximum two (2) inch lip equal on both sides of nose piece is permitted and may extend no farther back then the back side of the radiator. Lips on the hood are not allowed.
- 4.10 Belly pans are not allowed. A belly pan will be defined as any object or material that alters the airflow under the racecar.
- 4.11 Panel(s) in front of the right door next to the engine compartment is/are not allowed. **Panels under the deck area mounted horizontal or vertical are not allowed.**
- 4.12 Bodies with excessive damage (as determined by an official) will not be allowed to compete.
- 4.13 Spoilers are not allowed **unless utilizing Engine Option #4. Maximum material height of five (5) inches is permitted. Rear spoiler may not exceed the width of the rear deck and must be flush to the deck. A maximum of one (1) center support and a maximum of two (2) side supports may be attached to the front of the spoiler and may be a maximum of fifteen (15) inches long and six (6) inches tall.**
- 4.14 The rear deck lid and/or trunk area must be covered. Deck height may be a maximum of thirty-nine (39) inches – NO TOLERANCE. Must have an access panel no smaller than six (6) inches wide and twelve (12) inches long in front of fuel cell in the deck to view pull bar location. Drop decks are not allowed. Doors and quarter panels must be flush with deck. **Doors and quarter panels may not be concaved towards center of car.** Deck width may be a maximum of sixty-six (66) inches and must be the same from front to rear.
- 4.15 **A solid panel on the rear of the body is not required.**
- 4.16 Tires must remain the widest part of the racecar. No part of body may extend beyond the outside edge of the tires. Exception: The lower part of the left rear quarter panel's wheel opening's front edge may

extend a maximum one inch outside the tire but wheel opening must remain no smaller than outside diameter of tire.

- 4.17 Excluding hood and nose piece, body may extend no further forward than the back of the engine block. Exception: Bottom of door may extend a maximum of eight (8) inches ahead of rear of block.
- 4.18 A maximum five (5) inch plastic skirt on bottom of doors and quarter panels and nose piece is permitted. Body must remain a minimum of three (3) inches from ground. Engine covers are not allowed. Fins, wings, lips or other air spoilers (other than noted) are not allowed. Any approved lip(s) must be the same from side to side.

4.19 Bumpers:

- 4.19.1 Center of bumpers (front and rear) must be at least sixteen (16) inches from the ground and no more than twenty (20) inches from ground.
- 4.19.2 Both front and rear bumpers must be used, and must not have any sharp edges. Any inappropriate bumper will be disallowed by an official. Front bumper must be mounted from frame-end to frame-end with the bottom loop parallel to ground. Bumpers must be made of a minimum of one and one-quarter (1.25) inch diameter tubing with a minimum wall thickness of sixty-five one-thousandths (.065) inch and must be able to support the racecar if lifted by a tow vehicle. Top bar must be directly above bottom bar (not off-centered).
- 4.19.3 Rear bumpers and side rail bars must not extend beyond the width of the rear tires. Tires must be the widest part of body.
- 4.19.4 Rear bumpers may be constructed of tubing or flat stock, and must protect the fuel cell. Rear bumpers may be no more than two (2) inches wider than the body on each side and may not be open-ended (must wrap around and be connected to side rail bars).
- 4.19.5 Any aluminum of the nose may not extend outside of front bumper. Plastic valances and/or plastic nose pieces are permitted but no plastic may extend in front of the bumper. Plastic may flare past the sides of the bumper but all nose piece components must be a minimum of five (5) inches above the ground.
- 4.19.6 Front bumper may be a maximum width of 44 inches from outside to outside. Nose tin may have a maximum width of 42 inches at bottom. *Note: If it is between nose fins, it is considered to be the nose; if it separates from the hood, it is considered to be the nose.*

4.20 Appearance:

- 4.20.1 All racecars must be numbered with large legible numbers on both sides, on top and on the nose and rear panels. Numbers on the sides of the racecar should be in contrasting color from the body and be at least four (4) inches thick and at least eighteen (18) inches high. Top numbers should be at least four (4) inches thick and twenty-four (24) inches high.
- 4.20.2 Officials reserve the right, in the public image of the sport and/or the USRA, to assign, approve or disapprove any advertising, sponsorship or similar agreement in connection with any event. All cars must be neat appearing and are subject to approval of officials to compete. By competing in an event, all drivers agree to comply with the decisions of officials in this regard.

ARTICLE 5: ROLL CAGES

- 5.1 The main roll cage must consist of continuous hoops of round steel tubing, and must be acceptable to officials. Acceptable tubing is as follows: minimum one and one-half (1.5) inches diameter by ninety-five one-thousandths (0.095) inch wall thickness for main four point roll cage. **Any tubing measuring one and three-quarter (1.75) inches diameter will be allowed a tolerance on the wall thickness for tubing manufacturing imperfections. Any tubing under one and three-quarter (1.75) inches diameter will not be allowed any tolerance on wall thickness.** A minimum of three (3) driver side door bars must be parallel to ground and located perpendicular to the driver to provide maximum protection for the driver, but without causing undue difficulty in getting in or out of the racecar. Side bars must be welded to the front and the rear of the roll cage members. Driver side door bars and uprights must be at least one and one-half (1.5) inches in diameter at a minimum of eighty-three one-thousandths (0.083) of an inch wall thickness. **Steel door plate, 18 gauge or 0.049 inch minimum thickness, must be securely welded to outside of driver side door bars and cover area from top door bar to bottom door bar and from rear hoop down-post to five inches in front of seat.** Passenger side must have at least one cross door bar, horizontal or angled, minimum one and one-quarter (1.25) inch O.D. with eighty-three one thousandths (0.083) inch wall thickness, and one top horizontal door bar, minimum one and one-half (1.5) inch O.D. with eighty-three one thousandths (0.083) inch wall thickness.

- 5.2 Roll bars within the driver's reach must be padded with an accepted material as determined by an official. Fire retardant material is highly recommended.
- 5.3 Installation and workmanship must be acceptable to officials.
- 5.4 Must be frame-mounted in at least six (6) places.
- 5.5 Must consist of a configuration of front and rear hoops connected by tubing on the sides or side hoops.
- 5.6 With helmet on and driver securely strapped into the racing seat, top of driver's head must not protrude above the roll cage. **A cross bar in halo is required.**
- 5.7 Must have a protective screen or bars in front window opening in front of driver's face.
- 5.8 Protection of driver's feet utilizing a bar across the back of the engine with vertical bars and rub rails or similar protection is mandatory.
- 5.9 Brace bars forward of roll cage may not be higher than the stock hood height.
- 5.10 **Adjustable bars on the frame and/or roll cage are not allowed. Removable bars are permitted.**

ARTICLE 6: FRAME

- 6.1 Factory production complete full 1960 or newer parallel American passenger car frames only. Frames may be cut in rear only at a point not further than thirty-six (36) inches from center of rear end housing.
- 6.2 May only be altered for the installation of springs and shocks. Top of frame may not be altered for upper "A" frame clearance.
- 6.3 All components must be made of steel and be properly welded.
- 6.4 Must be full and complete on both sides, may not be widened or narrowed and must be able to support roll cage on both sides. All factory holes must be present for inspection. All measurements must meet the frame diagram tolerances listed or be within one-half (0.5) inch (either way) of OEM measurements on any measurement not listed on frame diagram – NO TOLERANCE.
- 6.5 Minimum height from ground is four (4) inches. Exception: Front cross member may be notched for radiator clearance only. Outside frame rails may not be raised. (See measurement "L" on frame diagram)
- 6.6 Jeep, Bronco or similar four-wheel drive frames are not allowed. Sports car frames are not allowed. Front-wheel-drives are not allowed.
- 6.7 Rear of frame may be altered to accept leaf or coil springs.
- 6.8 Hydraulic, ratchet or electric weight jacks are not allowed anywhere on the racecar. Aluminum jack bolts are not allowed.
- 6.9 Wheelbase must be a minimum of one-hundred eight (108) inches on both sides and a maximum of one-hundred twelve (112) inches on both sides (no tolerance).
- 6.10 Tubular front clips are not allowed.
- 6.11 Overall width of the racecar may not exceed seventy-eight (78) inches. Width shall be measured from the widest points on each side of the racecar (the tires).
- 6.12 Rear of engine (bell housing flange) must be mounted at least seventy-two (72) inches forward from the center line of the rear axle – NO TOLERANCE.

ARTICLE 7: COCKPIT, STEERING & SEAT

- 7.1 Loose objects and/or weights are not allowed.
- 7.2 Air bags are not allowed.
- 7.3 Rear view mirrors are not allowed.
- 7.4 Floor and firewall must be complete in the driver's compartment. Minimum 0.125 inch aluminum, or 0.060 inch steel, complete floor pan required. Interior sheet metal cannot be higher than or enclose a standard window opening. Sheet metal in the driver's compartment must be horizontal from the top of the driver shaft tunnel to the right side door bars or angle from the top of the drive shaft tunnel upwards to the top of the right side door bars. Driver must be able to exit the racecar from both sides.
- 7.5 Steering:**
 - 7.5.1 Must be OEM and remain within original bolt pattern for type of frame used. Idler arm, pitman arm and center link must match frame. Outer tie rod end and adjustment sleeve may be replaced with a heim end and steel tube.
 - 7.5.2 Rack and pinion is not allowed.
 - 7.5.3 **600 steering gear boxes are not allowed.**
 - 7.5.4 May be modified to suit driver, but must remain on left side of cockpit (no center steering).
 - 7.5.5 Quick-release metal coupling on steering wheel is mandatory. Plastic couplings are not allowed.

7.6 Seat:

- 7.6.1 Factory-manufactured racing seats are mandatory, and must be acceptable to officials.
- 7.6.2 Homemade aluminum, plastic or fiberglass seats are not allowed.
- 7.6.3 Must be properly installed and seat back cannot be moved back further than rear edge of quarter post.
- 7.6.4 High-back aluminum seats only. Full containment racing seats are strongly recommended.

ARTICLE 8: SUSPENSION

- 8.1 Front suspension must remain stock-type for the type of frame being used. Lower A frame must be unaltered stock stamped steel and in OEM location and remain OEM dimensions with OEM type bushings only. Mono ball or heim style bushings are not allowed. One-piece steel, rubber, polyurethane or nylon bushings only No offset or bearing type bushings allowed. Inner steel sleeve in bushing must be present. Screw-in ball joints are permitted. Front suspension travel limiting devices are not allowed. GM 1978-1988 metric "G" body frames are allowed to use Nova lower "A" frames.
- 8.2 Aluminum and/or titanium components are not allowed. Magnet must stick to all components Exception: aluminum cross shafts are permitted. Stainless steel is permitted. **Gun-drilled, tubular and/or hollow bolts or studs are not allowed anywhere on the racecar.**
- 8.3 Steel tube-type upper A-frames are permitted and may be moved.
- 8.4 Stock unaltered passenger car spindles only, must match side to side make and dimensions. Fabricated spindles are not allowed.
- 8.5 Front sway bars may be used. Must be made of steel and may be attached to the bottom A-frame using steel Heim joints. Must be solid full-length OEM.
- 8.6 A solid rear panhard bar or solid J-bar may be used. J-bar must be mounted to right side of pinion and go over the top of the driveshaft to left side of the chassis. Must be made of steel and may be attached by using a minimum three-quarter (0.75) inch i.d. steel Heim joint. Minimum length must be nineteen (19) inches measured from center of Heim to center of Heim.
- 8.7 Two-link suspension only. Four-link type suspensions are not allowed. All suspension bars and/or arms must remain solid and straight, a minimum fifteen (15) inches from center of Heim and must mount on the bottom side of rear end housing. Swing arms are not allowed. Solid pull bars only and centerline of pull bar must be mounted within one (1) inch of driveshaft centerline.
- 8.8 Suspension or rear-end parts, including jack bolts and mounting brackets, must be made of steel. Lift arm is not allowed. Spring and suspension covers are not allowed. Tarps and/or covers on racecar are not allowed outside of your pit area.
- 8.9 Floating suspensions are not allowed. All bird cages and/or brackets must be welded to the rear-end housing.
- 8.10 Safety/tether chains must be mounted vertically and solid to rear-end (not to any suspension parts). Right side spring must remain loose when rear-end is hanging off the ground if tethered. **Left side chain may utilize a rubber biscuit but no type of springs are allowed on chain.**
- 8.11 Shocks & Springs:**
 - 8.11.1 One (1) shock per wheel is permitted and **rear shocks** must be mounted within **twenty five(25)** degrees of vertical. Only conventional type (closed on one end) single shaft shocks are permitted. Rear end dampener shocks are not allowed. Rear shocks may be mounted on a weight-jack-type adjustable bolt.
 - 8.11.2 **Shock shaft must be able to compress all the way into shock body.**
 - 8.11.3 Shock covers are permitted but **may cover only front half of shock and must** be mounted directly to shock. Bump stops (internal or external) are not allowed. **A maximum one-half (0.5) inch thick rubber stopper only, mounted on the right front shock only for shock protection when bottomed out, is permitted. The rubber stopper must be mounted directly above a standard length heim on the shock with no spacers or shims allowed on shock or shock mount.**
 - 8.11.4 Steel shock mounting bolts only. Aluminum and/or titanium is not allowed.
 - 8.11.5 Coil-over, remote and/or air reservoir shocks are not allowed. Canister and/or adjustable shocks are not allowed. Bulb-type shocks are not allowed. Air shocks are not allowed. Aluminum shocks are not allowed. Inerter shocks, J-damper shocks, active mass damper shocks and/or through-rod-designed shocks are not allowed. Aluminum shaft guides are permitted.
 - 8.11.6 Bladder-type valves and/or Schrader valves are not allowed. Shocks shall be subject to claim, as outlined in Claim Procedures (see Article 19).

- 8.11.7 One spring slider on each rear wheel is permitted. Coil springs must be at least four and one-half (4.5) inches outside diameter. Steel springs only. Torsion bars are not allowed in rear. Spring rubbers are not allowed. Progressive, stacked and/or welded springs are not allowed.
- 8.11.8 Leaf Spring Rule: Must use steel, multi-leaf springs. Must be same number of full springs on each side (half springs are not allowed). Additional suspension components are not allowed. Adjustable lowering blocks are permitted.
- 8.11.9 Mono-Leaf Spring Rule: Must utilize coil springs centered on top of rear-end housing.
- 8.11.10 Must adhere to either Leaf Spring Rule or Mono-Leaf Rule. Mixing and matching is not allowed.
- 8.11.11 Optional: OEM Stock Suspension Rule: Must utilize stock OEM rear control arm mounts in stock locations for the frame being used. All components must be OEM and match the frame being used. Unaltered control arms only. Stock rubber, nylon or steel bushings only. Springs must remain in stock location on the top; lower perches must be welded to the rear end housing. Steel weight jacks only. Rear of engine (bell housing flange) must be mounted at least seventy (70) inches forward from the center line of the rear axle.

ARTICLE 9: ELECTRICAL SYSTEM

9.1 Battery:

- 9.1.1 Must be securely mounted inside frame rails and covered.
- 9.1.2 One (1) 12-volt battery only (no 16-volt batteries).
- 9.1.3 Voltage converters are not allowed.
- 9.1.4 All battery posts must be securely covered.

9.2 Ignition:

- 9.2.1 Must utilize OEM distributor and ignition. Stock-appearing coils, coil covers and modules only. Square coil covers are not allowed. Multiple spark ignitions are not allowed. Crank trigger ignitions are not allowed. GM external coils are not allowed. All ignition parts must remain out of the reach of the driver.
- 9.2.2 Kill switch required within easy reach of the driver. The switch must be clearly marked "OFF" and "ON".
- 9.2.3 GM must utilize OEM GM HEI distributor. Chrysler and Ford may use aftermarket HEI (bushing type only). Roller bearings are not allowed. Must utilize stock-type components.
- 9.2.4 Circuit board modules are not allowed.
- 9.3 Digital gauges are not allowed. Digital tachometers are permitted. Cameras pointing to any moving or suspension parts are not allowed. Except for memory recall tachometer, electronic monitoring computer devices capable of storing and/or transmitting information are not allowed.
- 9.4 Wiring elements must be accessible for technical inspection. Any racecar advancing spots and missing will be subject to disqualification.
- 9.5 All standard engines (see Rule 16.7) must utilize a soft-touch rev control box MSD part #8727CT with a 7,200 RPM maximum limit. All crate engines (see Rule 16.6) and concept engines (see rule 16.8) must utilize a soft-touch rev control box MSD part #8727CT with a 6200 RPM maximum limit This must be out of reach of the driver but easily accessible for inspection at all times. MSD part #8727CT rev control box is required with unaltered wiring harness and will be required on all race cars. Ground wire must be secured next to box and by itself visible for inspection.
- 9.6 Transponders must be mounted vertically on or behind engine mid-plate, less than two (2) feet from the ground and unobstructed by any metal.

ARTICLE 10: FUEL SYSTEM

10.1 Fuel:

- 10.1.1 Automotive gasoline, racing gasoline is permitted. Oxygenated fuel is not allowed; however an ethanol blend is allowed up to 85%. Additives of any kind are not allowed. Penalty for illegal fuel is loss of points, cash and awards earned for that event and subject to a fine.
- 10.1.2 May not be blended with ethers or other oxygenates, and may not be blended with aniline or its derivatives, nitro compounds or other nitro containing compounds.
- 10.1.3 Upper cylinder lubricants are not allowed.
- 10.2 Electric fuel pumps are not allowed. Belt driven fuel pumps are not allowed. Pumps must bolt to block in stock location.

10.3 Carburetor:

- 10.3.1 Must be naturally aspirated.

- 10.3.2 Fuel injection is not allowed.
- 10.3.3 Must be a gauge-legal Holley 500 CFM two-barrel (part #4412). HP carburetors are not allowed. Must be completely unaltered, however, an aftermarket metering block is permitted. Grinding and/or polishing of any kind is not allowed. All carburetor components must be for a Holley 500. Milling and/or grinding of throttle shaft is not allowed, and shaft must stay round. The choke and air horn may be removed (this is the only reworking permitted). Casting line at venturi must be present. Boosters must remain centered in venturi and may not be raised or lowered. Crate motors are permitted to use a Holley four-barrel carburetor.
- 10.3.4 One (1) two-barrel carburetor properly installed will be permitted.
- 10.3.5 A one (1) inch adapter plate or spacer is permitted. Distance between bottom of carburetor and top of intake manifold cannot exceed one and one-quarter (1.25) inch. Spacer thickness must remain the same front to back and side to side.
- 10.3.6 Carburetors shall be subject to claim, as outlined in Claim Procedures (see Article 19).
- 10.4 Fuel Cell:**
- 10.4.1 Must be commercially manufactured and must be mounted utilizing at least two (2) steel straps. Straps must be two (2) inches wide at all measuring points.
- 10.4.2 Must be enclosed in a steel container and must be protected in rear of axle by roll cage tubing mounted securely.
- 10.4.3 No part may be lower than protective tubing. Protective tubing must be no wider than six (6) inches on both sides. Fuel cell may be no lower than ten (10) inches from the ground.
- 10.4.4 Must have check valves. A ball-type, flapper or spring or filler rollover valve is mandatory for fuel cells without a positive seal filler neck/cap system.
- 10.4.5 Limited to a maximum capacity of thirty-two (32) gallons.

ARTICLE 11: TIRES & WHEELS

11.1 Wheels:

- 11.1.1 Must be fifteen (15) inches in diameter and eight (8) inches in width.
- 11.1.2 Bleeder valves are not allowed.
- 11.1.3 Must be reinforced steel only.
- 11.1.4 A steel bead lock may be used on the right side wheels only, and may be mounted on the outside of the wheel so long as it does not add to the overall width of the wheel.
- 11.1.5 Homemade mud caps are not allowed.
- 11.1.6 Wheel covers are permitted on right side wheels only. Inner mud plugs are permitted.
- 11.1.7 Wide five wheel adaptors are not allowed. **Steel lug nuts only are permitted.**
- 11.1.8 Spacer between hub and wheel is permitted, but must be made of aluminum only and overall width of racecar cannot exceed 78 inches.
- 11.1.9 **Added ballast to any wheel is not allowed.**

11.2 Tires:

- 11.2.1 The only tire permitted is the American Racer G60-15 KK704 (Short, Tall or X Tall). Tires must durometer 50 or harder at the conclusion of any race. Any tire not meeting this durometer reading is subject to having a tire sample sent in for chemical testing.
- 11.2.2 Softening is not allowed. Solvents of any kind are not allowed. Altering tires with any components or chemicals which alter the manufacturer's baseline-settings of the tire is not allowed.
- 11.2.3 Grooving and/or siping is permitted.
- 11.2.4 Sidewall markings must remain visible. Buffing and/or removing compound designations is not allowed.
- 11.2.5 **Added ballast to the inside of any tire is not allowed.**

11.3 Tire Testing Procedures:

- 11.3.1 Random GC (gas chromatography) scans may be performed to identify illegal substances. A GC scan should always be a peak in 19-20 minutes. If there is no peak, the driver will be disqualified. Driver may protest the GC scan results and request a mass spec test at the cost to the driver (usually around \$300). The mass spec test will reveal exactly what substance was used. The main peak of the tire should never be in half.
- 11.3.2 Traces of chemicals and/or excessive quantities of chemicals found to be outside the baseline on any test shall result in the penalties declared in Rule 2.15.5 plus an additional indefinite financial penalty and indefinite length of suspension. This penalty also applies to driver refusal of a tire test. Refusal of tire test shall be treated the same as an infraction. Official(s) may inspect any tire on the racecar and/or any tire

in possession of the driver in his/her pit area and/or hauler (in other words, if you have "doped" tires then do not even bring them to the track).

- 11.3.3 It is strongly recommended that all drivers use only soap and water. Baking tires will not eliminate traces of illegal substances. The USRA will aggressively test for illegal substances and will levy severe punishment for infractions relating to tires.

ARTICLE 12: BRAKING SYSTEM

- 12.1 Must be operating on all four wheels and must lock up all four wheels during inspection.
- 12.2 Must have caliper and rotor on all four wheels. Vented rotors are required on front and rear wheels.
- 12.3 Electronic brake actuators are not allowed. Brake shut-offs are not allowed.
- 12.4 Calipers may not be lightened, must be OEM and must be made of steel and must match front to front and rear to rear.
- 12.5 Rotors must be steel and may not be lightened, scalloped, slotted or drilled. Rotors may be re-drilled for different bolt patterns or larger studs. Oil bath hubs are not allowed.
- 12.6 Front-to-rear brake bias is permitted (no left to right).
- 12.7 Brake floaters are not allowed.
- 12.8 Brake lines must be visible.
- 12.9 Must maintain minimum OEM dimension for hubs, rotors, pads and calipers.

ARTICLE 13: DRIVE SHAFT

- 13.1 A loop is required and must be constructed of at least one-quarter (0.25) inch by two (2) inches solid steel. Loop must be mounted no more than six (6) inches from the front of the drive shaft tube. Alternatively, two (2) loops of one-quarter (0.25) inch by one (1) inch solid steel fastened to cross member are permitted.
- 13.2 Must be a minimum two (2) inches in diameter.
- 13.3 Must be painted white.
- 13.4 Aluminum drive shafts are not allowed.
- 13.5 Carbon fiber drive shafts are permitted but must be painted white.

ARTICLE 14: TRANSMISSION

- 14.1 OEM three-speed, four-speed and five-speed and automatic production-types are permitted. With engine running and racecar in stationary position, driver must be able to engage racecar in gear and then move forward and then backward at time of inspection.
- 14.2 "In and out" boxes are not allowed. Ball spline transmissions are not allowed.
- 14.3 May all be clutch-operated or an OEM automatic with a coupler. May use a hand or clutch pedal operated ball valve for neutral.
- 14.4 Aftermarket transmissions are permitted.
- 14.5 Approved aftermarket transmissions are Bert (Part #LMZ/GEN II), Brinn (Part #70001), Falcon (Part #60100) and RaceGator (Part #140002/140002-C) and Mitchell Machine Bullet Tranny with internal clutch.
- 14.6 Clutch must be inside of bell housing for OEM production-type transmissions (except as noted in Rule 14.4).
- 14.7 Starter must bolt to engine block or factory location.
- 14.8 One (1) forward gear and one (1) reverse gear must be in working order, plus a neutral position, and must be able to be shifted by driver.
- 14.9 Aluminum flywheel is permitted. Must have full-sized explosion proof, aluminum or steel bell housing. Aluminum must be SFI approved (Note: GM bell housing is not SFI approved). Flywheel must bolt to crankshaft. Clutch must bolt to flywheel, a minimum six and one-quarter (6.25) inch clutch.
- 14.10 Automatic and aftermarket transmissions must have a guard two-hundred seventy (270) degrees around flex plate or flywheel, and must be constructed of at least one-quarter (0.25) inch steel. Alternatively, automatic and/or aftermarket transmissions may utilize an SFI-certified aftermarket guard. Flex plates must be SFI certified.
- 14.11 Internal clutches are not allowed except for approved aftermarket transmissions.

ARTICLE 15: REAR-END

- 15.1 Any passenger car- or truck-type is permitted. Aluminum is not allowed except lowering blocks, axle cap, U-joint caps and drive plate.
- 15.2 Nine (9) inch Ford rear-end is permitted (floater recommended).
- 15.3 Quick change rear-end is permitted with steel axles and steel axle tubes only. Must use a ten (10) inch ring gear and minimum one (1) inch wide solid spur gears.
- 15.4 Cambered rear-ends are not allowed (one-piece drive flange only).
- 15.5 Traction devices are not allowed (includes Gold Track, True Track or similar type components).
- 15.6 Rear of engine (bell housing flange) must be mounted at least seventy-two (72) inches forward from the center line of the rear axle – NO TOLERANCE.

ARTICLE 16: ENGINE

- 16.1 Overflow tubes must be directed toward the ground and inside the frame rails.
- 16.2 Radiator must be mounted in front of engine. Aluminum pulleys and radiators are permitted.
- 16.3 All belt driven components must be mounted on front of engine. Electric water pumps and/or fans are not allowed. Engine oil coolers are not allowed. Air pumps are not allowed.
- 16.4 Exhaust & Mufflers:**
 - 16.4.1 Round tube headers only. Tri-Y headers are not allowed. All primary tubes must enter one collector at the same point. Crate engine and concept engine must use a non-stepped header only. Header wrap is not allowed.
 - 16.4.2 Exhaust system and/or mufflers must be mounted in such a way as to direct spent gases away from the cockpit and away from areas of possible fuel spillage. Exhaust through body panels or fenders is not allowed.
 - 16.4.3 Mufflers are recommended. Mufflers may be required at track's discretion.
 - 16.4.4 Exhaust sensors, merge collectors, dividing collectors, venturi collectors and/or extension cones are not allowed. Collector extension and/or muffler and turn down may not exceed twenty-four (24) inches and must maintain a consistent inside diameter.
 - 16.4.5 Zoomies, Crossovers and/or 180's are not allowed.
 - 16.4.6 Oil pan evac systems are permitted but must enter exhaust header from the side of the collector only. External pump systems are not allowed.
- 16.6 OPTION #1 – Crate Engine:**
 - 16.6.1 GM Performance Parts (GPP) factory-sealed CT350 Chevy small block crate engine (Part No. 88958602 or 19258602): includes four-bolt-main block, 9.5:1 hypereutectic pistons, cast iron crankshaft, GM iron Vortec cylinder heads, high-rise dual-plane intake manifold, 8-quart single kick-out circle track oil pan, valve cover kit with breather tube and breather, unique dual-pattern cam and special "kool nut" rocker arm nut design.
 - 16.6.2 May utilize one (1) Holley 4-barrel carburetor. Use of a spacer between carburetor and intake is optional, but spacer may be no more than one (1) inch thick and may not be throttle bore adjustable. Aerosol carburetors are not permitted. Carburetors shall be subject to claim (crate to crate only) as outlined in Claim Procedures (see Article 19).
 - 16.6.3 Must utilize soft-touch rev control box with a 6200 RPM limit. This must be out of reach of the driver but easily accessible for inspection at all times. Any driver caught altering the chip or ignition system in any way so as to defeat the chip rule shall receive a 30-day suspension, loss of all track and national points for the night and a \$1,000 fine for the first offense. Second offense shall be a one-year suspension, loss of all track and national points for the season and a \$2,000 fine.
 - 16.6.4 Must have "Crate" sticker on racecar or crate engine is claimable. Any driver running a "Standard" engine with a "Crate" sticker will be disqualified. Any driver running with a crate motor will not be eligible to claim in that season. Any driver that claims a standard engine and switches to crate engine will be eligible to be claimed.
 - 16.6.5 Must be unaltered and sealed from factory at appropriate points (intake, head, timing chain cover and oil pan) with approved GPP break-off bolts. Any altered, damaged or missing GPP break-off bolts will result in driver being disqualified from that event, loss of all track and national points accumulated up to, and including, the date of the offense, and a \$2,000 fine and fourteen (14) day suspension from all USRA-sanctioned events. Second offense carries a \$5,000 fine and one (1) year suspension.
 - 16.6.6 GM seal bolt exception is USRA, USMTS or approved rebuild seals (call 515-835-9946 for verification).

16.6.7 Crate Engine is not subject to claim.

16.7 OPTION #2 – Standard Engine:

- 16.7.1 Must be stock appearing. Any American make is permitted. Absolutely no changes allowed. Must use stock firing order for that make and model (GM to GM, Ford to Ford, etc.). Titanium is not allowed.
- 16.7.2 May be a maximum of 360 cubic inches. (370 c.i. for Chrysler).
- 16.7.3 Must be a maximum 9.5:1 compression. Exception: 302-, 305-, 307- and 318-cubic-inch engines may run 10.5:1 compression. Only flat top or dished pistons are permitted.
- 16.7.4 Must appear strictly stock for that model and make and in the original mounts. Parts for 400 cubic inches or larger are not allowed. Stroke must match block. Block casting number must remain visible.
- 16.7.5 Only stock appearing crankshafts are permitted. Lightweight cranks are not allowed. No undercut, bull nosed, gun drilled or knife edge crankshafts allowed.
- 16.7.6 Lightweight, aluminum and/or fluid dampeners are not allowed
- 16.7.7 GM five and seven-tenths (5.7) inch or six (6) inch rods are permitted. Must be stock appearing I-beam non-polished rod. Aluminum or light weight is not allowed. Cap screw rods are permitted
- 16.7.8 A minimum one (1) inch plug above the oil level in the side of the oil pan is recommended. If not utilizing a plug, oil pan will have to be removed at time of inspection.
- 16.7.9 Only stock, unaltered two-barrel low rise cast iron intake manifolds or Approved aluminum intakes are permitted. Approved aluminum intakes are GM - Edelbrock (#2101 or #2701) or Weiand (#7547 or #7547-1); Ford - Edelbrock (#2121 or #2181 or #2665) or Weiand (#7515 or #8023 or #7516); Chrysler – Edelbrock (#2176) or Weiand (#7545 or #8022). Porting, polishing or port machining is not allowed. Bowtie, aftermarket, SVO and W2, marine, VORTEC or other special production intake manifolds are not allowed. External cooler lines from back of intake to front of intake is permitted.
- 16.7.10 Cast iron stock production or aftermarket steel stock replacement heads are permitted. Porting and/or polishing is not allowed. GM cars must utilize 76cc heads (approved head numbers are 336, 339, 388, 441, 454, 487, 624, 813, 882, 991 and 993). Aftermarket head numbers are: GM – EQ Part #CC167ES2 or #CH350I; Dart Part #10024267 or #10024360; World Products Part #043600 or #042670; Ford – World Products Part #53030; Chrysler – EQ Part #CH138B; RHS/Indy Part #20300 or #20301. Heads may be flat milled to reach the 9.5:1 compression rule. Valve size no larger than 2.02 intake and 1.60 exhaust. VORTEC heads are not allowed. Beehive valve springs are not allowed.
- 16.7.11 Screw-in studs, guide plates and poly-locks are permitted.
- 16.7.12 Roller cams and lifters are not allowed. Roller Rocker arms are not allowed (stock-type stamped steel rocker arms or cast steel rocker arms only). Roller tip rocker arms are permitted. Chryslers may utilize OEM steel shaft rockers but may not exceed one hundred twenty (120) pounds of valve spring seat pressure and must maintain OEM valve spring dimensions. Under valve cover pressurized valve train oiling systems are not allowed.
- 16.7.13 Mushroom lifters are not allowed (stock diameter only). Must match make and model.
- 16.7.14 Stud girdles are not allowed.

16.8 OPTION #3 – Concept Engine:

- 16.8.1 Chevrolet 350 cubic inch, 9.5:1 compression engines only. Stroke must match block. 4.060 maximum bore.
- 16.8.2 Stock OEM crankshafts must match block. Aftermarket crankshafts allowed are Eagle Part #103503480, #103503480CM, #103523480 or #435034805700; Scat Part #910442, #910526, or #4-350-3480-5700; Manley Part #190310; and PEP Part #DG3182D. Resizing journals to 0.030 inches under maximum is permitted.
- 16.8.3 Stock OEM connecting rods must be 5.7 and match block. Aftermarket rods allowed are Eagle Part #SIR5700BBLW or #SIR5700BPLW; and Scat Part #35700P, #25700P, #25700 or #35700. **602 Crate Engine rods are permitted.**
- 16.8.4 Pistons allowed are Icon Part #SO2733 or #SO2733LCA; Mahle Part #WIS50030F05, #WIS50040F05 or #WIS50060F05; **and CP-Carrillo part #BC1021-030W, 035W, 040W, 045W or 060W.** Must use wrist pin that came with piston. Must use 1.5mm, 1.5mm, 3mm piston rings. **602 Crate Engine pistons are permitted.**
- 16.8.5 Aftermarket and/or splayed main caps are not allowed.
- 16.8.6 Aftermarket blocks are not allowed. **602 Crate Engine blocks are permitted.**
- 16.8.6 Grinding, polishing and/or coating of any internal or external engine parts is not allowed.
- 16.8.7 Altering lifter bores are not allowed. Lifter bore valley vent tubes are not allowed.
- 16.8.8 Balancing permitted by drilling only.

- 16.8.9 Only steel oil pans with one-inch inspection hole are permitted. Only wet sump systems are permitted.
- 16.8.10 Only flat tappet hydraulic camshafts with 0.450-inch maximum lift are permitted.
- 16.8.11 Only steel and stock diameter lifters are permitted. Lift must collapse (0.100 inch minimum).
- 16.8.12 **Cast iron stock production or aftermarket steel stock replacement heads are permitted. Porting and/or polishing is not allowed. GM heads must utilize 76cc heads (approved head numbers are 336, 339, 388, 441, 454, 487, 624, 813, 882, 991 and 993). Aftermarket head numbers are EQ (part #CC167ES2 or #CH350I)** Maximum valve size is one and ninety-four one-hundredths (1.94) inch intake and one and one-half (1.5) inch exhaust and eleven thirty-seconds (11/32) inch diameter, non-hollow valve stems. Intake valves must weigh a minimum one hundred three (103) grams. Exhaust valves must weigh a minimum eighty-seven (87) grams. Titanium is not allowed in motor.
- 16.8.13 Only stock diameter valve springs are permitted. Beehive valve springs are not allowed. Only stock steel spring retainers are permitted.
- 16.8.14 Only stock-type, stamped steel 1.5 ratio fulcrum rocker arms are permitted. Full roller and/or roller tips are not allowed.
- 16.8.15 Intake manifold must be an unaltered Edelbrock 2701.
- 16.8.16 Must utilize the Speedway carb spacer (part #N 135-1960) **or Summit carb spacer (part numbers SUM G1412 or SUM G1404)** with a maximum three-eighths (3/8) inch of gasket material between carb and intake.
- 16.8.17 Any Holley four-barrel carburetor is permitted.
- 16.8.18 Only non-stepped headers are permitted. Must follow all header rules (See Rule 16.4).
- 16.8.19 Any stock steel balancer with a minimum diameter of six and three-quarter (6.75) inches and a minimum thickness of one and one thousand eight hundred and seventy-five ten-thousandths (1.1875) inches is permitted. Fluid dampeners are not allowed.
- 16.8.20 Must utilize a rev limiter with a maximum setting of 6,200 RPM (See Rule 9.5).
- 16.8.21 Overall racecar weight must be a minimum **two-thousand six hundred (2,600)** pounds with twenty-five (25) pounds mounted in front of the mid-plate.
- 16.8.22 Must have "Concept" sticker on racecar, otherwise engine is claimable. Any driver utilizing a concept engine will not be eligible to claim in that season. Any driver that claims a standard engine and switches to concept engine will be eligible to be claimed.
- 16.8.23 Concept engines are not subject to claim.
- 16.8.24 All USRA fuel rules apply.

16.9 Engine Option #4 – Utilized Spoiler Engine: You may utilize a five (5) inch spoiler if the following rules are adhered to (all other USRA B-Mod rules apply):

- **Body:** An eight (8) inch rear filler panel must be utilized.
- **Rear Suspension:** A thirteen (13) inch maximum vertical rear spring centered on rear end with solid spring cups is required. A sixteen (16) inch minimum rear suspension link and twenty-three (23) inch minimum straight pan hard bar mounted behind rear end housing is required. Rear shocks must be mounted behind rear end housing. Rear chains, if used, must be mounted solid to axle housing and frame, and must have slack with rear end at ride height.
- **Engine:** Standard Engines and Crate Engines only (no Concept Engines). Stepped headers are not allowed. Maximum compression of 9.0:1 with a 6,800 RPM maximum limit on Standard Engines. E85 fuel is not allowed. Cold air boxes are not allowed.
- **Rear End:** Quick change rear ends are not allowed. Full spool and/or lightened rear end gears are not allowed.
- **Transmission:** Clutchless transmissions are not allowed (all transmission gears must function).
- **Tires and Wheels:** Tire grooving is not allowed. Only three (3) or four (4) inch back set wheels are allowed. Wheel spacers are not allowed.

ARTICLE 17: WEIGHT

- 17.1 The overall weight of the racecar shall be measured at the conclusion of an event with the driver in the cockpit, wearing complete racing apparel. All racecars must display weight at which it will compete on both windshield posts. Must be two (2) inches tall and in contrasting color to the racecar. Any racecar not displaying their weight will be required to weigh the maximum weight for this class and required to add any weight in any location required in this class.

17.2 Overall weight of the racecar must be a minimum of two-thousand five hundred (2,500) pounds for standard and crate engines. Overall weight of the racecar must be a minimum of **two-thousand six hundred (2,600)** pounds for the concept engine.

17.3 Ballast:

17.3.1 May not be mounted in cockpit, outside of body or hood area, **or on any rotating parts.**

17.3.2 Must be securely mounted, painted white and clearly marked with the car number.

17.3.3 Must be attached with at least two (2) one-half (0.5) inch bolts with a maximum of one hundred (100) pounds per mounting. Any ballast weighing twenty-five (25) pounds or less may be mounted with one (1) one-half (0.5) inch bolt.

17.3.4 May not be attached to rear bumper.

ARTICLE 18: SAFETY

18.1 It is recommended that each racecar have built-in fire extinguishing equipment, but cannot be of the dry powder type (must be Halon 1211 or equivalent).

18.2 Drivers should have in their pit area as part of their equipment, at all times, a fully charged dry chemical, Halon (or its equivalent) fire extinguisher. Ten- or thirteen-pound fire extinguishers are recommended.

18.3 Driver must wear required helmet, fire suit and five-point safety harness whenever the racecar is on the racetrack. This includes during track packing, warm ups, hot laps and races.

18.4 Helmets are mandatory and must be certified SA2010 or SA2015.

18.5 Helmet must accompany driver and racecar at time of inspection.

18.6 Complete one- or two-piece fire suits of a flame retardant nature are mandatory.

18.7 Fire-resistant gloves and shoes are mandatory. Fire-resistant socks are recommended.

18.8 The use of a five- six- or seven-point driver restraint system (safety belts, sub-belt and shoulder harness) is required. Factory-type shoulder belts or straps are not allowed. The use of a seven-point driver restraint system is recommended.

18.9 Metal to metal buckles are required on shoulder and seat belts.

18.10 Shoulder harness must be mounted securely to the main roll cage.

18.11 Where the belt passes through the seat edges, a grommet must be installed, rolled and/or padded to prevent cutting of the belt.

18.12 Driver restraint system must be less than three (3) years of age past the date of manufacture. It is recommended that the driver restraint system be no more than two (2) years of age past the date of manufacture.

18.13 Full-size window net mounted in the left side driver's window opening is required. Window net mounts must be welded to the roll cage. All bars around the driver must have approved roll bar padding. Approved racing arm restraints are recommended.

18.14 Fire-resistant safety neck collars are mandatory.

18.15 Absolutely no plastic except from edge of firewall to body skin and inner wheel tub to body skin.

ARTICLE 19: CLAIMING PROCEDURES

19.1 Any driver possessing a valid USRA license may have the opportunity to execute a claim on the cylinder heads and intake manifold, shocks or carburetor of another driver's racecar. Crate Engines and Concept Engines are not claimable. Drivers utilizing a Crate Engine or Concept Engine are not eligible to claim another driver's cylinder heads and intake manifold. Any driver running with a Crate Engine or Concept Engine will not be eligible to claim another driver's cylinder heads and intake manifold in that season. Any driver that claims a standard engine and switches to a Crate Engine or Concept Engine will be eligible to have their cylinder heads and intake manifold claimed.

19.2 The first four (4) finishers in the main event must drive their racecars directly to the designated claim area at the conclusion of the main event, and are subject to being claimed by any other driver that finishes fifth or lower and finishes on the same lap as the winner. Any of the top four finishers that do not go to the claim area will be disqualified, but are still subject to being claimed.

19.3 Claims must be made within five (5) minutes of the completion of the main event. Claimed items must be removed at the racetrack and within one (1) hour after claimed driver accepts the claim.

19.4 Driver making claim must drive his/her race car immediately after finish of feature, under its own power, directly to the claim area.

- 19.5 Claiming driver must present license and cash to official overseeing the claim area at the time that the driver declares his/her intention to claim. The cash price of the claim for cylinder heads and intake manifold shall be \$500. The cash price of the claim for carburetors shall be \$300 or \$150 and exchange. **Only four-barrel for four-barrel and/or two-barrel for two-barrel claims are permitted.** The cash price of the claim for shocks shall be \$50 per shock. Drivers claiming shocks may claim one or more shocks during a single claim.
- 19.6 The cylinder heads and intake manifold claim includes both cylinder heads and intake manifold, rocker arm studs and guide plate, valves, valve springs, retainers and keepers, and intake bolts. This claim does not include carburetor spacer, valve covers, rocker arms, pushrods, thermostat and thermostat housing, any fittings, adapters, studs or head bolts.
- 19.7 Claiming driver shall select from the first four (4) finishers in the main event, and must declare that choice to the official overseeing the claim area. If the claiming driver decides at that time that he/she does not wish to execute the claim, he/she will nonetheless be charged one claim. If multiple drivers declare an intention to claim, the driver finishing farthest back in the main event will select first. If the claimed driver is utilizing a non-claimable engine, the claiming driver may not choose another driver and will not be charged a claim.
- 19.8 Driver is permitted one (1) claim per event, regardless of the outcome of that claim.
- 19.9 Only drivers, car owners and officials are permitted in the designated claim area. Any other participants associated with that racecar that enter the claim area will be subject to disqualification, fine and/or suspension.
- 19.10 Only a driver may claim, and only the claimed driver or car owner may agree to accept or refuse the claim. The first statement of acceptance or rejection of the claim by the claimed driver or car owner is binding.
- 19.11 Any driver or car owner refusing to accept a claim will forfeit all cash and contingency winnings for that event.
- 19.12 Any driver or car owner refusing to accept a claim forfeits his/her right to make a claim in any USRA event for a period of one (1) year from the date of refusal.
- 19.13 Any driver or car owner refusing to accept a claim will forfeit all USRA points (national and track) accumulated up to, and including, the event at which the claim was made.
- 19.14 First refusal to accept a claim will result in that driver and car owner being suspended from all USRA events for thirty (30) days and until a \$1,000 fine is paid and received at USRA headquarters. Second refusal to accept a claim will result in that driver and car owner being suspended from all USRA events for one (1) year and until a \$5,000 fine is paid and received at USRA headquarters.
- 19.15 In the event of a dispute between driver and car owner whether to accept or refuse a claim, the decision of the driver shall overrule that of the car owner.
- 19.16 Any driver found to be making a claim for another person will lose all USRA points (national and track) accumulated to date for the entire season, all cash and contingency winnings for that event, and will be suspended from all USRA events for thirty (30) days and until a \$1,000 fine is paid and received at USRA headquarters.
- 19.17 Sabotage of claimed parts will result in driver being suspended from all USRA events for fourteen (14) days and until a \$1,000 fine is paid and received at USRA headquarters. Driver will also forfeit all USRA points (national and track) accumulated up to, and including, the event at which the sabotage occurred. Furthermore, driver will forfeit the privilege to make a claim for a period of one (1) year from the date on which the sabotage occurred.
- 19.18 Driver may claim a maximum of three (3) times during the calendar year.
- 19.19 After making an accepted claim, driver must finish in the top four (4) of a main event and reinstate his/her license. Cost is \$25 for reinstatement of license. Driver will not be eligible to make another claim unless license is reinstated.
- 19.20 Cost for replacement of a lost license is \$25.
- 19.21 Driver must compete in a minimum of three (3) consecutive events prior to the event at which he/she makes a claim.
- 19.22 The USRA reserves the right to disallow any claim at their discretion.
- 19.23 Drivers utilizing a provisional starting position in the main event are not allowed to make a claim in that event.
- 19.24 At their discretion, officials reserve the option to claim the cylinder heads and intake manifold, shock or carburetor of any racecar.

- 19.25 Drivers will be eligible to make a claim during the first event of the season. After one event, driver must have raced in previous events before Rule 19.21 applies.
- 19.26 Disqualification shall not affect a legal claim. Claimed parts will be removed and transferred prior to any penalties being assessed. All involved claimed parts and related parts are subject to technical inspection and any illegal parts are subject to all fines and penalties but do not void the claim.

AMENDMENTS

January 19, 2018

- Added Summit carb spacer (part numbers SUM G1412 or SUM G1404) to Rule 16.8.16.

March 6, 2018

- Added The rubber stopper must be mounted directly above a standard length heim on the shock with no spacers or shims allowed on shock or shock mount to Rule 8.11.3.

March 7, 2018

- Added Panels under the deck area mounted horizontal or vertical are not allowed to Rule 4.11.
- Added unless utilizing Engine Option #4. Maximum material height of five (5) inches is permitted. Rear spoiler may not exceed the width of the rear deck and must be flush to the deck. A maximum of one (1) center support and a maximum of two (2) side supports may be attached to the front of the spoiler and may be a maximum of fifteen (15) inches long and six (6) inches tall to Rule 4.13.
- Added Doors and quarter panels may not be concaved towards center of car to Rule 4.14.
- Added Rule 16.9.

March 30, 2018

- Added Standard Engines and Crate Engines only (no Concept Engines) to Rule 16.9.

July 16, 2018

- Removed with twenty-five (25) pounds of weight mounted in front of the mid-plate from Rule 14.4.
- Changed to 6,800 RPM maximum limit on Standard Engines in Rule 16.9 (Engines).
- Removed with twenty-five (25) pounds mounted in front of the mid-plate, plus an additional twenty-five (25) pounds mounted in front of the mid-plate if utilizing an approved aftermarket transmission (see rule 14.4 from Rule 17.2).

##

United States Racing Association, Inc. (USRA)
P.O. Box 905, Webster City, IA 50595
Office: (515) 832-6000 | Fax: (515) 832-7958 | www.usracing.com
Darlo Mulder, Competition Director: (515) 835-9946 | tech@usracing.com

Copyright © 2017-2018 United States Racing Association. All rights reserved.