

2024 USRA B-MOD RULES

Published November 13, 2023
Amended February 26, 2024



THE RULES AND/OR REGULATIONS SET FORTH HEREIN ARE DESIGNED TO PROVIDE FOR THE ORDERLY CONDUCT OF RACING EVENTS AND TO ESTABLISH MINIMUM ACCEPTABLE REQUIREMENTS FOR SUCH EVENTS. THESE RULES SHALL GOVERN THE CONDITION OF SPEEDWAY EVENTS AND, BY PARTICIPATING IN THESE EVENTS, ALL RACEWAY COMPETITORS ARE DEEMED TO HAVE COMPLIED WITH THESE RULES. NO EXPRESS OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM PUBLICATION OF, OR COMPLIANCE WITH THESE RULES AND REGULATIONS. THEY ARE INTENDED AS A GUIDE FOR THE CONDUCT OF THE SPORT AND IN NO WAY ARE A GUARANTEE AGAINST INJURY OR DEATH TO PARTICIPANTS, SPECTATORS OR OTHERS.

References are made throughout these regulations requiring and/or recommending that particular products meet certain specifications. These products are manufactured to meet or exceed certain criteria and are labeled as such upon satisfying those criteria. Any change to these products voids that certification. Under no circumstances may any certified product be altered from the "as manufactured" condition or such certification is voided.

Changes and additions to the 2023 USRA B-Mod rules are underlined and highlighted in red. Changes made for grammatical purposes or to improve clarity are not highlighted. All participants and officials are expected and required to additionally be familiar with the definitions and details in the USRA General Rules, Regulations & Procedures.

The United States Racing Association shall hereafter be simply referred to as the USRA throughout the rules description. USRA official(s) shall include all personnel employed as an official by the participating racetrack.

USRA rules shall apply at all events. All participants are subject to the rules of the USRA and are expected to know the rules. These rules are a guideline as to what is permitted and/or not allowed. If these rules do not explicitly say it is permitted, then you must contact the USRA to identify if the part in question is permitted for competition.

TABLE OF CONTENTS

- Article 1: Body
- Article 2: Roll Cages
- Article 3: Frame
- Article 4: Cockpit, Steering & Seat
- Article 5: Suspension
- Article 6: Electrical System
- Article 7: Fuel System
- Article 8: Tires & Wheels
- Article 9: Braking System
- Article 10: Drive Shaft
- Article 11: Transmission
- Article 12: Rear End
- Article 13: Engine
- Article 14: Weight
- Article 15: Safety
- Article 16: Protest Procedures
- Article 17: Alternative Rules
- Amendments

ARTICLE 1: BODY

- 1.1 Plastic and/or composite body panels are not allowed with the exception of the rear quarter panels and doors. Rear quarter and doors may be constructed from a fire retardant plastic or composite material.

- 1.2 An aluminum half-windshield may be used on driver's side of the front window opening only, but may not extend more than six (6) inches past the steering wheel.
- 1.3 Stock appearing front window support units must be used (painted roll bars are not acceptable substitutes). Front window may have a support of no more than twenty (20) inches at bottom, going straight up to top.
- 1.4 A minimum window opening of twelve (12) inches must be maintained on all four window openings (front, back, left and right).
- 1.5 Streamlining at top of windshield is not allowed. Bodies must have standard appearing windshield opening and corner post must follow standard configuration.
- 1.6 Original roof line of vehicle (parallel to deck, front to back and side to side) must be maintained with a maximum of five (5) inches of slope from rear to front. No more than one (1) inch stiffener permitted at the rear of the roof and must turn down perpendicular to the ground. A maximum one (1) inch roof lips on outside edge of roof are permitted. A maximum four (4) inch vertical sides on the roof are permitted. Fiberglass roofs are permitted. Aluminum roofs are permitted but must remain flat and may not be concaved.
- 1.7 Sail panels must be solid and of matching design with matching styles on both sides of racecar. Sail panel may be no farther forward than the driver's seat and no farther back than rear of decking and no higher than the roof. Sail panel must be mounted within one (1) inch of the outer edge of deck and flush with the outer edge of roof. Sail panels, side to side, may have no more than four (4) inches of variance in material length when measured from roof line to deck.
- 1.8 Sail panels may have no more than four (4) inch consistent bow from top to bottom. A maximum eighteen (18) inches of sail panel along the roof and maximum five (5) inches tall at rear of decking and must be a straight line from back edge of roof to back edge of deck when the sail panel is held flat. Leading edge must within two inches of 90 degrees from roof to quarter panel.
- 1.9 Hood may be no more than two (2) inches above decking and must be sealed off from driver. Reverse hood rake is not allowed. Hood must be level or slope forward toward nose of racecar. Lips on the hood are not allowed. Hood must be flat from side to side—bowed and/or concaved designs are not allowed.
- 1.10 Belly pans are not allowed. A belly pan will be defined as any object or material that alters the airflow under the racecar.
- 1.11 Panel(s) in front of the right door next to the engine compartment is/are not allowed. Panels under the deck area mounted horizontal or vertical are not allowed.
- 1.12 Bodies with excessive damage (as determined by an official) will not be allowed to compete.
- 1.13 Spoilers are not allowed.
- 1.14 The rear deck lid and/or trunk area must be covered. Deck height may be a maximum of thirty-nine (39) inches—NO TOLERANCE. Must have an access panel no smaller than six (6) inches wide and twelve (12) inches long in front of fuel cell in the deck to view pull bar location. Drop decks are not allowed. Deck may be a maximum length of one hundred twenty (120) inches from rear of engine. Deck must remain parallel to the frame and chassis and the same width from front to back and front of deck must be level to ground from side to side. Deck may be skewed to the right within four inches of parallel to motor measured at rear of deck. (see measurement "W" in body diagram). Deck may not be concaved. Deck may have a maximum total slope of six (6) inches with a maximum of three (3) inches of slope from racing seat to rear of deck as measured from the ground. Doors and quarter panels must be flush with deck. Doors and quarter panels must be a minimum twenty-two (22) inches and a maximum thirty-six (36) inches in material length. Doors and quarter panels must remain outside of outside frame rails. Deck width may be a maximum of sixty-six (66) inches and must be the same from front to rear. The rear edge of the rear quarter panels must be square to top edge of quarter panel and may not extend past the rear of the decking or placed under the decking.
- 1.15 Maximum overall width of nose is forty-two (42) inches top and bottom. Nose must remain flat, parallel to the deck and may not be concaved. Two (2) inch nose fins are permitted along both sides of the nose. Nose fins may not pass the leading edge of radiator or continue past leading edge of hood. All aluminum of the nose (including the fins) must be completely inside the outer edges of the bumper. Nose fins must match side to side. If it is between nose fins, it is the nose; if it separates from the hood, it is the nose. Maximum nose length is forty-two (42) inches as measured from center of lower ball joint—NO TOLERANCE. Plastic valances and/or nose pieces are permitted (P.N. MD3M21100). When using a plastic nose, the upper nose filler must have a horizontal brace every twelve (12) inches to prevent the panel from becoming concaved. Concaved noses are not allowed with any material used.

- 1.16 Tires must remain the widest part of the racecar. No part of body may extend beyond the outside edge of the tires. Exception: The lower part of the left rear quarter panel's wheel opening's front edge may extend a maximum one inch outside the tire but wheel opening must remain no smaller than outside diameter of tire.
- 1.17 Excluding hood and nose piece, body may extend no further forward than the back of the engine block. Exception: Bottom of door may extend a maximum of eight (8) inches ahead of rear of block.
- 1.18 A maximum five (5) inch plastic skirt on bottom of doors and quarter panels and nose piece is permitted. Body must remain a minimum of three (3) inches from ground and nose must remain a minimum of five (5) inches from the ground. Engine covers are not allowed. Fins, wings, lips or other air spoilers (other than noted) are not allowed. A maximum one-half (0.5) inch break for rigidity on body panels is permitted. Any approved lip(s) must be the same from side to side..

1.19 Bumpers:

- 1.19.1 Center of bumpers (front and rear) must be at least sixteen (16) inches from the ground and no more than twenty (20) inches from ground.
- 1.19.2 Both front and rear bumpers must be used and must not have any sharp edges. Any inappropriate bumper will be disallowed by an official. Front bumper must be mounted from frame-end to frame-end with the bottom loop parallel to ground. Bumpers must be made of a minimum of one and one-quarter (1.25) inch diameter tubing with a minimum wall thickness of sixty-five one-thousandths (.065) inch and must be able to support the racecar if lifted by a tow vehicle. Top bar must be directly above bottom bar (not off-centered).
- 1.19.3 Rear bumpers and side rail bars must not extend beyond the width of the rear tires. Tires must be the widest part of body.
- 1.19.4 Rear bumpers may be constructed of round tubing and must protect the fuel cell.
- 1.19.5 Any aluminum of the nose may not extend outside of front bumper. Plastic valances and/or plastic nose pieces are permitted but no plastic may extend in front of the bumper. Plastic may flare past the sides of the bumper but all nose piece components must be a minimum of five (5) inches above the ground.
- 1.19.6 Front bumper may be a maximum width of **forty-six (46)** inches from outside to outside.
- 1.19.7 Bumper may be no farther forward than forty-two (42) inches as measured from the center of the lower ball joints.

1.20 Appearance:

- 1.20.1 All racecars must be numbered with large legible numbers on both sides, on top and on the nose and rear panels. Numbers on the sides of the racecar should be in contrasting color from the body and be at least four (4) inches thick and at least eighteen (18) inches high. Top numbers should be at least four (4) inches thick and twenty-four (24) inches high.
- 1.20.2 Officials reserve the right, in the public image of the sport and/or the USRA, to assign, approve or disapprove any advertising, sponsorship or similar agreement in connection with any event. All cars must be neat appearing and are subject to approval of officials to compete. By competing in an event, all drivers agree to comply with the decisions of officials in this regard.

ARTICLE 2: ROLL CAGES

- 2.1 The main roll cage must consist of continuous hoops of round steel tubing and must be acceptable to officials. Acceptable tubing is as follows: minimum one and one-half (1.5) inches diameter by ninety-five one-thousandths (0.095) inch wall thickness for main four point roll cage. Any tubing measuring one and three-quarter (1.75) inches diameter will be permitted a minimum wall thickness of eighty-three one-thousandths (.083) inch. Any tubing under one and three-quarter (1.75) inches diameter will be required to be a minimum ninety-five one-thousandths (0.095) inch wall thickness tubing. Sliding and/or slip joint roll bar unions associated to the main roll cage are not allowed. A minimum of three (3) driver side door bars must be parallel to ground and located perpendicular to the driver to provide maximum protection for the driver, but without causing undue difficulty in getting in or out of the racecar. Side bars must be welded to the front and the rear of the roll cage members. Driver side door bars and uprights must be at least one and one-half (1.5) inches in diameter at a minimum of eighty-three one-thousandths (0.083) of an inch wall thickness. Steel door plate, 18 gauge or forty-nine one-thousandths (0.049) inch minimum thickness, must be securely welded to outside of driver side door bars and cover area from top door bar to bottom door bar and from rear hoop down-post to five inches in front of seat. Passenger side must have at least one cross door bar, horizontal or angled, minimum one and one-quarter (1.25) inch O.D.

- with eighty-three one thousandths (0.083) inch wall thickness, and one top horizontal door bar, minimum one and one-half (1.5) inch O.D. with eighty-three one thousandths (0.083) inch wall thickness.
- 2.2 Roll bars within the driver's reach must be padded with an accepted material as determined by an official. Fire retardant material is highly recommended.
 - 2.3 Installation and workmanship must be acceptable to officials.
 - 2.4 Must be frame-mounted in at least six (6) places.
 - 2.5 Must consist of a configuration of front and rear hoops connected by tubing on the sides or side hoops meeting the minimum tubing dimensions listed in Rule 2.1.
 - 2.6 With helmet on and driver securely strapped into the racing seat, top of driver's head must not protrude above the roll cage. A cross bar in halo is required.
 - 2.7 Must have a protective screen or bars in front window opening in front of driver's face.
 - 2.8 Protection of driver's feet utilizing a bar across the back of the engine with vertical bars and rub rails or similar protection is mandatory.
 - 2.9 Brace bars forward of roll cage may not be higher than the stock hood height.
 - 2.10 Adjustable bars on the frame and/or roll cage are not allowed. Removable bars are permitted.
 - 2.11 Roll cages not meeting these rules and regulations will be subject to cash fines and associated penalties.

ARTICLE 3: FRAME

- 3.1 Factory production complete full-perimeter 1960 or newer parallel American passenger car frames only. Frames may be cut in rear only at a point equal to or behind rear of engine.
- 3.2 May only be altered for the installation of springs and shocks. Top of frame may not be altered for upper "A" frame clearance.
- 3.3 All components must be made of steel and be properly welded.
- 3.4 Must be full and complete on both sides, may not be widened or narrowed and must be able to support roll cage on both sides. All factory holes must be present for inspection. All measurements must meet the frame diagram tolerances listed or be within one-half (0.5) inch (either way) of OEM measurements on any measurement not listed on frame diagram—NO TOLERANCE.
- 3.5 Minimum height from ground is four (4) inches. Exception: Front cross member may be notched for radiator clearance only. Outside frame rails may not be raised. (See measurement "L" on frame diagram)
- 3.6 Rear of frame may be altered to accept leaf or coil springs.
- 3.7 Hydraulic, ratchet or electric weight jacks are not allowed anywhere on the racecar. Aluminum jack bolts are not allowed.
- 3.8 Wheelbase must be a minimum of one-hundred eight (108) inches on both sides and a maximum of one-hundred twelve (112) inches on both sides (no tolerance).
- 3.9 Tubular front clips are not allowed.
- 3.10 Overall width of the racecar may not exceed seventy-eight (78) inches. Width shall be measured from the widest points on each side of the racecar (the tires).
- 3.11 Rear of engine (bell housing flange) must be mounted at least seventy-two (72) inches forward from the center line of the rear axle—NO TOLERANCE.

ARTICLE 4: COCKPIT, STEERING & SEAT

- 4.1 Loose objects and/or weights are not allowed.
- 4.2 Air bags are not allowed. Rear view mirrors are not allowed.
- 4.3 Other than the gas pedal, brake pedal and front-to-rear brake bias, any knobs, handles or levers used for adjustment of carburetor, ignition timing and/or suspension is not allowed.
- 4.4 Floor and firewall must be complete in the driver's compartment. Minimum 0.125 inch aluminum, or 0.060 inch steel, complete floor pan required. Interior sheet metal cannot be higher than or enclose a standard window opening. Sheet metal in the driver's compartment must be horizontal from the top of the driver shaft tunnel to the right side door bars or angle from the top of the drive shaft tunnel upwards to the top of the right side door bars. Driver must be able to exit the racecar from both sides.
- 4.5 Steering:**
 - 4.5.1 Must be OEM and remain within original bolt pattern for type of frame used. Idler arm, pitman arm and center link must match frame. Outer tie rod end and adjustment sleeve may be replaced with a heim end and steel tube.
 - 4.5.2 Rack and pinion is not allowed.

- 4.5.3 600 steering gear boxes are not allowed.
- 4.5.4 May be modified to suit driver but must remain on left side of cockpit (no center steering).
- 4.5.5 Quick-release metal coupling on steering wheel is mandatory. Plastic couplings are not allowed.
- 4.6 Seat:**
- 4.6.1 Factory-manufactured racing seats are mandatory and must be acceptable to officials.
- 4.6.2 Homemade aluminum, plastic or fiberglass seats are not allowed.
- 4.6.3 Must be installed with minimum three-eighth (3/8)-inch fasteners and washers and seat back may not be moved back further than rear edge of quarter post.
- 4.6.4 High-back aluminum seats only. Full containment racing seats are strongly recommended.

ARTICLE 5: SUSPENSION

- 5.1 Front suspension must remain stock-type for the type of frame being used. Lower A frame must be unaltered stock stamped steel and in OEM location and remain OEM dimensions with OEM type bushings only. Mono ball or heim style bushings are not allowed. One-piece steel, rubber, polyurethane or nylon bushings only No offset or bearing type bushings allowed. Inner steel sleeve in bushing must be present. Screw-in ball joints are permitted. GM 1978-1988 metric "G" body frames are allowed to use Nova lower "A" frames. Front and/or rear suspension travel limiting devices are not allowed except for tether chains (see Rule 5.10). Front and/or rear suspension must travel freely in both directions from ride height measured at the shock.
- 5.2 Aluminum and/or titanium components are not allowed. Magnet must stick to all components Exception: aluminum cross shafts are permitted. Stainless steel is permitted. Gun-drilled, tubular and/or hollow bolts or studs are not allowed anywhere on the racecar.
- 5.3 Steel tube-type upper A-frames are permitted and may be moved but pivot points must remain on the top of the frame rail.
- 5.4 Stock unaltered passenger car spindles only, must match side to side make and dimensions. Fabricated spindles and/or steering arms are not allowed.
- 5.5 Front sway bars may be used. Must be made of steel and may be attached to the bottom A-frame using steel Heim joints. Must be solid full-length OEM.
- 5.6 A solid rear panhard bar or solid J-bar may be used. J-bar must be mounted to right side of pinion and go over the top of the driveshaft to left side of the chassis. Must be made of steel and may be attached by using a minimum three-quarter (0.75) inch i.d. steel Heim joint. Minimum length must be nineteen (19) inches measured from center of Heim to center of Heim.
- 5.7 Two-link suspension only. Four-link type suspensions are not allowed. All suspension bars and/or arms must remain solid and straight, a minimum fifteen (15) inches from center of Heim and must mount on the bottom side of rear end housing. Swing arms are not allowed. Solid pull bars only and centerline of pull bar must be mounted above driveshaft and within one (1) inch of driveshaft centerline. Lift arm is not allowed.
- 5.8 Suspension or rearend parts, including jack bolts and mounting brackets, must be made of steel. Spring and suspension covers are not allowed. Tarps and/or covers on racecar are not allowed in tech area.
- 5.9 Floating suspensions are not allowed. All bird cages and/or brackets must be welded to the rearend housing.
- 5.10 A tether chain is permitted on front and rear suspension. Chain must be mounted from lower A-frame to frame or cage on front end and on top of axle tube to frame or cage on rear end. Chains must be mounted vertical and solid and must remain loose at ride height. Only left side rear chain may utilize a rubber biscuit. Springs of any kind are not allowed on chains. Frame or cage rearend travel stops are not allowed (*Exception: under slung chassis and tether chains*).
- 5.11 Shocks & Springs:**
- 5.11.1 One (1) shock per wheel is permitted and rear shocks must be mounted within twenty-five (25) degrees of vertical. Only conventional type (closed on one end) single shaft shocks are permitted. Rear end dampener shocks are not allowed. Rear shocks may be mounted on a weight-jack-type adjustable bolt.
- 5.11.2 Shock shaft must be able to compress all the way into shock body. Shock shaft must move in both directions from its installed position at ride height. Shock cannot preload the spring.
- 5.11.3 Shock covers are permitted but may cover only front half of shock and must be mounted directly to shock. Bump stops (internal or external) are not allowed. Shock rubber stoppers are not allowed.
- 5.11.4 Steel shock mounting bolts only. Aluminum and/or titanium is not allowed.

- 5.11.5 Bladder-type and/or Schrader valves are not allowed. Coil-over, remote and/or air reservoir shocks are not allowed. Canister and/or adjustable shocks are not allowed. Bulb-type shocks are not allowed. Air shocks are not allowed. Aluminum shocks are not allowed. Inerter shocks, J-damper shocks, active mass damper shocks and/or through-rod-designed shocks are not allowed. Dummy shocks are not allowed. Aluminum shaft guides are permitted.
- 5.11.6 Shocks shall be subject to protest, as outlined in Protest Procedures (see Article 16).
- 5.11.7 One spring slider on each rear wheel is permitted. Coil springs must be at least four and one-half (4.5) inches outside diameter. Steel springs only. Torsion bars are not allowed in rear. Spring rubbers are not allowed. Progressive, tapered, stacked and/or welded springs are not allowed.
- 5.11.8 Leaf Spring Rule: Must use steel, multi-leaf springs. Must be same number of full springs on each side (half springs are not allowed). Additional suspension components are not allowed. Adjustable lowering blocks are permitted.
- 5.11.9 Mono-Leaf Spring Rule: Must utilize coil springs centered on top of rearend housing.
- 5.11.10 Must adhere to either Leaf Spring Rule or Mono-Leaf Rule. Mixing and matching is not allowed.

ARTICLE 6: ELECTRICAL SYSTEM

6.1 Battery:

- 6.1.1 Must be securely mounted inside frame rails and covered.
- 6.1.2 One (1) 12-volt battery only (no 16-volt batteries).
- 6.1.3 Voltage converters are not allowed.
- 6.1.4 All battery posts must be securely covered.
- 6.1.5 Alternators are allowed with a maximum 14-volt output, and must be wired directly to the battery (not to an ON/OFF switch).

6.2 Ignition:

- 6.2.1 Must utilize OEM distributor and ignition. Stock-appearing coils, coil covers and modules only. Square coil covers are not allowed. Multiple spark ignitions are not allowed. Crank trigger ignitions are not allowed. GM external coils are not allowed. All ignition parts must remain out of the reach of the driver.
- 6.2.2 Kill switch required within easy reach of the driver. The switch must be clearly marked "OFF" and "ON."
- 6.2.3 GM must utilize OEM GM HEI distributor. Chrysler and Ford may use aftermarket HEI (bushing type only). Roller bearings are not allowed. Must utilize stock-type components.
- 6.2.4 Open circuit board modules are not allowed.
- 6.3 Digital gauges are not allowed. Digital tachometers are permitted. Cameras pointing to any moving parts, suspension parts and/or gauges are not allowed. Except for memory recall tachometer, electronic monitoring computer devices capable of storing and/or transmitting information are not allowed.
- 6.4 Wiring elements must be accessible for technical inspection. Any racecar advancing spots and missing will be subject to disqualification.
- 6.5 All standard engines (see Rule 13.7) must utilize a soft-touch rev control box MSD part #8727CT with a 7,000 RPM maximum limit. All crate engines (see Rule 13.6) must utilize a soft-touch rev control box MSD part #8727CT with a 6200 RPM maximum limit. All concept engines (see rule 13.8) must utilize a soft-touch rev control box MSD part #8727CT with a 6500 RPM maximum limit. This must be out of reach of the driver but easily accessible for inspection at all times. A lexan window above ignition box for easy viewing of the rev limiter is highly recommended. MSD part #8727CT rev control box is required with unaltered wiring harness and will be required on all race cars. Ground wire must be visible for inspection and it is recommended that it be mounted near or on the distributor. Any driver deemed to have altered the rev limiter and/or ignition system in any way to defeat the rev limiter rule shall receive a minimum 30-day suspension, loss of all track, regional and national points for the night and a \$1,000 fine for the first offense. Second offense shall be a minimum one (1)-year suspension, loss of all track, regional and national points for the year and a \$2,000 fine.
- 6.6 Transponders must be mounted vertically on or behind engine mid-plate, less than two (2) feet from the ground and unobstructed by any metal.

ARTICLE 7: FUEL SYSTEM

7.1 Fuel:

- 7.1.1 Automotive gasoline, racing gasoline is permitted. Oxygenated fuel is not allowed; however an ethanol blend is allowed up to 85%. Additives of any kind are not allowed. Penalty for illegal fuel is loss of points, cash and awards earned for that event and subject to a fine.
- 7.1.2 May not be blended with ethers or other oxygenates and may not be blended with aniline or its derivatives, nitro compounds or other nitro containing compounds. Fuel is tested and must pass using a Digitron dielectric meter. It is the responsibility of the driver and/or owner to have fuel tested.
- 7.1.3 Upper cylinder lubricants are not allowed.
- 7.2 Electric fuel pumps are not allowed. Belt driven fuel pumps are not allowed. Pumps must bolt to block in stock location.
- 7.3 Carburetor:**
 - 7.3.1 Must be naturally aspirated.
 - 7.3.2 Fuel injection is not allowed. Aerosol carburetors are not allowed.
 - 7.3.3 The **Standard Engine** must utilize a gauge-legal, unaltered Holley (or Holley-type) 500 CFM two-barrel (part #4412). HP and/or XP carburetors are not allowed. Aftermarket metering blocks are permitted. Grinding and/or polishing of any kind is not allowed. All carburetor components must be for a Holley 500. Milling and/or grinding of throttle shaft is not allowed, and shaft must stay round. The choke and air horn may be removed (this is the only reworking permitted). Casting line at venturi must be present. Boosters must remain centered in venturi and may not be raised or lowered. Annular discharge boosters are not allowed.
 - 7.3.4 **Crate engines and concept engines** are permitted to use a Holley 4150 Series four-barrel carburetor. HP carburetors are permitted. This carburetor has no size requirements but must remain to function as the 4150 series carburetor was designed and must utilize Holley type boosters. Vacuum secondary carburetors are not allowed. Annular discharge boosters are not allowed.
 - 7.3.5 A one (1) inch adapter plate or spacer is permitted. Distance between bottom of carburetor and top of intake manifold cannot exceed one and one-quarter (1.25) inch. Spacer thickness must remain the same front to back and side to side.
 - 7.3.6 Carburetors shall be subject to protest, as outlined in Protest Procedures (see Article 16).
- 7.4 Fuel Cell:**
 - 7.4.1 Must be commercially manufactured and must be mounted utilizing at least two (2) steel straps. Straps must be two (2) inches wide at all measuring points.
 - 7.4.2 Must be enclosed in a steel container and must be protected in rear of axle by roll cage tubing mounted securely.
 - 7.4.3 No part may be lower than protective tubing. Protective tubing must be no wider than six (6) inches on both sides. Fuel cell may be no lower than ten (10) inches from the ground.
 - 7.4.4 Must have check valves. A ball-type, flapper or spring or filler rollover valve is mandatory for fuel cells without a positive seal filler neck/cap system.
 - 7.4.5 Limited to a maximum capacity of thirty-two (32) gallons.

ARTICLE 8: TIRES & WHEELS

8.1 Wheels:

- 8.1.1 Must be fifteen (15) inches in diameter and eight (8) inches in width.
- 8.1.2 Bleeder valves are not allowed.
- 8.1.3 Must be reinforced steel only.
- 8.1.4 A steel bead lock may be used on the right side wheels only and may be mounted on the outside of the wheel so long as it does not add to the overall width of the wheel.
- 8.1.5 Homemade mud caps are not allowed.
- 8.1.6 Wheel covers are permitted on right side wheels only. Inner mud plugs are permitted.
- 8.1.7 Wide five wheel adaptors are not allowed. Steel lug nuts only are permitted.
- 8.1.8 Spacer between hub and wheel is permitted but must be made of aluminum only and overall width of racecar cannot exceed seventy-eight (78) inches measured from the top of left tire to the bottom of the right tire (at widest part).
- 8.1.9 Added ballast to any wheel is not allowed.
- 8.1.10 Solid and/or non-spoked wheels are not allowed.

8.2 Tires:

- 8.2.1 The only tire permitted is the American Racer G60-15 KK704 (Short, Tall or X Tall). Tires must durometer 50 or harder at the conclusion of any race. Any tire not meeting this durometer reading is subject to having a tire sample sent in for chemical testing.
- 8.2.2 Softening is not allowed. Solvents of any kind are not allowed. Altering tires with any components or chemicals which alter the manufacturer's baseline-settings of the tire is not allowed.
- 8.2.3 Grooving and/or siping is permitted.
- 8.2.4 Sidewall markings must remain visible. Buffing and/or removing compound designations is not allowed.
- 8.2.5 Added ballast to the inside of any tire is not allowed.
- 8.2.6 Plastic wrap on tires is permitted in your pit area but must be removed before leaving your pit stall.
- 8.3 Tire Testing Procedures:**
 - 8.3.1 Random GC (gas chromatography) scans may be performed to identify illegal substances. A GC scan should always be at peak in 19-20 minutes. If there is no peak, the driver will be disqualified. Driver may protest the GC scan results and request a mass spec test at the cost to the driver (usually around \$300). The mass spec test will reveal exactly what substance was used. The main peak of the tire should never be in half.
 - 8.3.2 Traces of chemicals and/or excessive quantities of chemicals found to be outside the baseline on any test is automatic disqualification. First offense shall result in loss of all points accumulated for the season, forfeiture of all prize money earned for the event, up to a \$5,000 fine and an indefinite suspension from USRA-sanctioned events. Driver will not be permitted to compete in any future USRA-sanctioned event until fine is paid in full.
 - 8.3.3 It is strongly recommended that all drivers use only soap and water. Baking tires will not eliminate traces of illegal substances. The USRA will aggressively test for illegal substances and will levy severe punishment for infractions.

ARTICLE 9: BRAKING SYSTEM

- 9.1 Must be operating on all four wheels and must lock up all four wheels during inspection.
- 9.2 Must have caliper and rotor on all four wheels. Caliper and rotor must be standard size and weight. Vented rotors are required on front and rear wheels.
- 9.3 Electronic brake actuators are not allowed. Brake shut-offs are not allowed.
- 9.4 Calipers may not be lightened, must be OEM, made of steel and must match front to front and rear to rear. Brake pads may not be altered or lightened and must match side to side.
- 9.5 Rotors must be steel and may not be lightened, scalloped, slotted or drilled. Rotors may be re-drilled for different bolt patterns or larger studs. Oil bath hubs are not allowed.
- 9.6 Front-to-rear brake bias is permitted (no left to right).
- 9.7 Brake floaters are not allowed.
- 9.8 Brake lines must be visible.
- 9.9 Must maintain minimum OEM dimension for hubs, rotors, pads and calipers.

ARTICLE 10: DRIVE SHAFT

- 10.1 A loop is required and must be constructed of at least one-quarter (0.25) inch by two (2) inches solid steel. Loop must be mounted no more than six (6) inches from the front of the drive shaft tube. Alternatively, two (2) loops of one-quarter (0.25) inch by one (1) inch solid steel fastened to cross member are permitted.
- 10.2 Must be a minimum two (2) inches in diameter.
- 10.3 Must be painted white.
- 10.4 Aluminum drive shafts are not allowed.
- 10.5 Carbon fiber drive shafts are permitted but must be painted white.

ARTICLE 11: TRANSMISSION

- 11.1 OEM three-speed, four-speed and five-speed and automatic production-types are permitted. With engine running and racecar in stationary position, driver must be able to engage racecar in gear and then move forward and then backward at time of inspection.
- 11.2 "In and out" boxes are not allowed. Ball spline transmissions are not allowed.
- 11.3 May all be clutch-operated or an OEM automatic with a coupler. May use a hand or clutch pedal operated ball valve for neutral.

- 11.4 Aftermarket transmissions are permitted. Approved aftermarket transmissions are Bert (Part #LMZ/GEN II), Brinn (Part #70001), Brinn Predator (Part #70600), Falcon (Part #60100) and RaceGator (Part #140002/140002-C), Jerico (Part# JER0021) and Mitchell Machine Bullet Tranny with internal clutch. Ball Spline transmissions are not allowed.
- 11.5 Clutch must be inside of bell housing for OEM production-type transmissions (except as noted in Rule 11.4).
- 11.6 Starter must bolt to engine block or factory location.
- 11.7 One (1) forward gear and one (1) reverse gear must be in working order, plus a neutral position, and must be able to be shifted by driver.
- 11.8 Aluminum flywheel is permitted. Must have full-sized explosion proof, aluminum or steel bell housing. Aluminum must be SFI approved (*Note: GM bell housing is not SFI approved*). Flywheel must bolt to crankshaft. Clutch must bolt to flywheel, a minimum six and one-quarter (6.25) inch clutch.
- 11.9 Must have approved scatter shield or blanket. Scatter shield may be constructed of one-eighth (0.125) inch by three (3) inch steel, two-hundred seventy (270) degrees around flex plate or flywheel. Alternatively, automatic and/or aftermarket transmissions may utilize an SFI-certified aftermarket guard. Flex plates must be SFI certified.
- 11.11 Internal clutches are not allowed except for approved aftermarket transmissions.

ARTICLE 12: REAREND

- 12.1 Any passenger car- or truck-type is permitted. Aluminum is not allowed except lowering blocks, axle cap, U-joint caps and drive plate.
- 12.2 Nine (9) inch Ford rearend is permitted (floater recommended).
- 12.3 Quick change rearend is permitted with steel axles and steel axle tubes only. Must use a ten (10) inch ring gear and minimum one (1) inch wide solid spur gears.
- 12.4 Cambered rearends are not allowed (one-piece drive flange only).
- 12.5 Traction devices are not allowed (includes Gold Track, True Track or similar type components).
- 12.6 Rear of engine (bell housing flange) must be mounted at least seventy-two (72) inches forward from the center line of the rear axle—NO TOLERANCE.
- 12.7 Frame- or cage-mounted, forward and/or backward rearend travel stops are not allowed.

ARTICLE 13: ENGINE

- 13.1 Overflow tubes must be directed toward the ground and inside the frame rails.
- 13.2 Radiator must be mounted in front of engine. Aluminum pulleys and radiators are permitted.
- 13.3 All belt driven components must be mounted on front of engine. Electric water pumps and/or fans are not allowed. Engine oil coolers are not allowed. Air pumps are not allowed.
- 13.4 Offset must be within two (2) inches of centerline of front cross member (front and rear of engine). Engine must remain square in chassis or rear of engine may be skewed to the left only and must be within Rule 1.14.
- 13.5 Must be a minimum of eleven (11) inches from ground to front center of crankshaft.
- 13.4 Exhaust & Mufflers:**
 - 13.4.1 Tri-Y headers are not allowed. Only round tube headers are permitted. Stainless steel headers are not allowed. All primary tubes must enter one collector at the same point. Concept Engines must utilize non-stepped headers only. Standard Engines and Crate Engines may utilize stepped headers. Header wrap is not allowed.
 - 13.4.2 Exhaust system and/or mufflers must be mounted in such a way as to direct spent gases away from the cockpit and away from areas of possible fuel spillage. Exhaust through body panels or fenders is not allowed.
 - 13.4.3 Mufflers are recommended. Mufflers may be required at track's discretion.
 - 13.4.4 Exhaust sensors, merge collectors, dividing collectors, venturi collectors and/or extension cones are not allowed. Collector extension and/or muffler and turn down may not exceed twenty-four (24) inches and must maintain a consistent inside diameter.
 - 13.4.5 Zoomies, Crossovers and/or 180s are not allowed.
 - 13.4.6 Oil pan evac systems are permitted but must enter exhaust header from the side of the collector only. External pump systems are not allowed.
- 13.6 OPTION #1 – Crate Engine:**

- 13.6.1 GM Performance Parts (GPP) CT350 "602" Chevy small block crate engine only. This engine may be rebuilt and is not required to be sealed however this engine must remain unaltered and must utilize the unaltered listed part numbers and follow the listed guide lines. CT350 four-bolt-main block only, hypereutectic pistons P/N 12514101/88894280, GM connecting rod P/N 10108688, cast iron crankshaft P/N 10243070,14088526, GM balancer P/N 19260269/19301706. GM iron Vortec cylinder heads P/N 12529093/12691728, high-rise dual-plane intake manifold P/N 12366573, 602 valve cover P/N 25534359. Unaltered GM camshaft P/N 24502476 only. GM lifter P/N 523270. GM push rod P/N 14095256. GM rocker arm P/N 10089648. Rocker arm nut P/N 19210731. GM valves P/N 10241743 intake/12550909 exhaust. GM Valve spring P/N 10212811. GM valve spring retainer P/N 10241744. GM timing gears P/N 340235/10128346 and chain P/N 14088783. GM oil pump P/N 93442037. GM head gasket P/N 10105117 must be utilized. Any other brand of gaskets may be used for the rest of the engine. The block may be decked to a minimum 9.020 inches deck height. The crankshaft line bore may be corrected. Maximum cylinder bore size is 4.008 inches. Minimum crankshaft journal size 0.010 inch under standard size. The maximum cylinder head resurfacing allowed is 0.005 inch. All valve and seat size and angles must remain stock. Standard three-angle valve job is permitted. Modifications below valve seat land are not allowed. Grinding, polishing, painting and/or coating of internal engine parts is not allowed. Lifter bore valley vent tubes are not allowed. Lifter bores may not be altered. Any steel 8-quart single kick-out circle track oil pan is allowed. If motor is not sealed than a minimum one-inch sight plug above the oil level in the side of the oil pan is required. If not utilizing a one-inch plug, oil pan may have to be removed for inspection. All other 602 Crate Engine specifications must be followed.
- 13.6.2 May utilize one (1) Holley 4150 Series four-barrel carburetor (see Article 7.3.4). Use of a spacer between carburetor and intake is optional, but spacer may be no more than one (1) inch thick and may not be throttle bore adjustable. Aerosol carburetors are not permitted. Carburetors shall be subject to protest as outlined in Protest Procedures (see Article 16).
- 13.6.3 Must utilize soft-touch rev control box with a 6,200 RPM limit. This must be out of reach of the driver but easily accessible for inspection at all times. Any driver caught altering the chip or ignition system in any way so as to defeat the chip rule shall receive a 30-day suspension, loss of all track and national points for the night and a \$1,000 fine for the first offense. Second offense shall be a one-year suspension, loss of all track and national points for the season and a \$2,000 fine.
- 13.6.4 A factory sealed Crate Engine is not subject to engine protests but must have a prominently displayed "Crate" decal affixed near the A pillar. Any unsealed crate engine is subject to protests. Any driver running with a sealed Crate Engine will not be eligible to protest engines in that season. Any driver that protests a Standard Engine and switches to a sealed Crate Engine will be eligible to be protested.
- 13.7 OPTION #2 – Standard Engine:**
- 13.7.1 Must be stock appearing. Any American make is permitted. Absolutely no changes allowed. Must use stock firing order for that make and model (GM to GM, Ford to Ford, etc.). Titanium is not allowed.
- 13.7.2 May be a maximum of 360 cubic inches. (370 c.i. for Chrysler).
- 13.7.3 Must be a maximum 9.5:1 compression. Only flat top or dished pistons are permitted.
- 13.7.4 Must appear strictly stock for that model and make and in the original mounts. Parts for 400 cubic-inch or larger engines are not allowed. Stroke must match block. Approved aftermarket blocks are permitted. Approved aftermarket blocks include DART #31161111 or Brodix #BRS400035842 or GM #12480047 or World Products #084010.
- 13.7.5 Only stock appearing crankshafts are permitted. Lightweight cranks are not allowed. No undercut, bull nosed, gun drilled or knife edge crankshafts allowed.
- 13.7.6 Lightweight, aluminum and/or fluid dampeners are not allowed
- 13.7.7 GM five and seven-tenths (5.7) inch or six (6) inch rods are permitted. Must be stock appearing I-beam non-polished rod. Only standard size rod journals and wrist pins (Chevrolet rods 2.100/.927) are permitted. Aluminum and/or light weight is not allowed. Cap screw rods are permitted.
- 13.7.8 A minimum one (1) inch plug above the oil level in the side of the oil pan is recommended. If not utilizing a one (1) inch plug, oil pan may have to be removed at time of inspection.
- 13.7.9 Only stock, unaltered two-barrel low rise cast iron intake manifolds or Approved aluminum intakes are permitted. Approved aluminum intakes are GM - Edelbrock (#2101 or #2701) or Weiand (#7547 or #7547-1); Ford - Edelbrock (#2121 or #2181 or #2665) or Weiand (#7515 or #8023 or #7516); Chrysler – Edelbrock (#2176) or Weiand (#7545 or #8022). Porting, polishing and/or powder coating or port machining is not allowed. Bowtie, aftermarket, SVO and W2, marine, VORTEC or other special

production intake manifolds are not allowed. External cooler lines from back of intake to front of intake is permitted.

- 13.7.10 Cast iron stock production or aftermarket steel stock replacement heads are permitted. Porting and/or polishing is not allowed. GM cars must utilize 76cc heads (approved head numbers are 336, 339, 388, 441, 454, 487, 624, 813, 882, 991 and 993). Aftermarket head numbers are GM – EQ Part #CC167ES2 or #CH350I; Dart Part #10024267 or #10024360; World Products Part #043600 or #042670; Ford – World Products Part #53030; Chrysler – EQ Part #CH318B; RHS/Indy Part #20300 or #20301. Heads may be flat milled to reach the 9.5:1 compression rule. Valve size no larger than 2.02 intake and 1.60 exhaust. VORTEC heads are not allowed. Beehive valve springs are not allowed.
- 13.7.11 Screw-in studs, guide plates and poly-locks are permitted.
- 13.7.12 Valve spring seat pressure may not exceed 130 pounds and open pressure may not exceed three hundred fifty (350) pounds—NO TOLERANCE. Roller cams and lifters are not allowed. Steel or aluminum stock ratio full roller rocker arms are permitted if the valve spring rule is utilized. Stock-type stamped steel rocker arms or cast stamped steel rocker arms are required if the valve spring rule is not utilized. Roller tip rocker arms are permitted with any valve spring. Any diameter valve spring is permitted. Beehive valve springs are not allowed. Chryslers may utilize OEM steel shaft rockers but may not exceed one hundred twenty (120) pounds of valve spring seat pressure and must maintain OEM valve spring dimensions. Under valve cover pressurized valve train oiling systems are not allowed.
- 13.7.13 Mushroom lifters are not allowed (stock diameter only). Must match make and model.
- 13.7.14 Stud girdles are not allowed.
- 13.7.15 Must utilize a rev limiter with a maximum setting of 7,000 RPM (See Rule 6.5).

13.8 OPTION #3 – Concept Engine:

- 13.8.1 Must be stock appearing. Any American make is permitted. Absolutely no changes allowed. Must use stock firing order for that make and model (GM to GM, Ford to Ford, etc.). Titanium is not allowed.
- 13.8.2 May be a maximum of 360 cubic inches. (370 c.i. for Chrysler).
- 13.8.3 Must be a maximum 9.5:1 compression. Only standard weight (minimum 450 grams) flat top or dished pistons are permitted. Must use standard weight wrist pins (minimum 130 grams). Must use minimum 1.5mm, 1.5mm, 3mm piston rings. Maximum six one hundredths (.06) inch oversized allowed.
- 13.8.4 Aftermarket and splayed main cap blocks are not allowed. Grinding, polishing, painting or coating of internal engine parts are not allowed. Altering lifter bores are not allowed. Lifter bore valley vent tubes are not allowed. Block casting number must remain visible. Approved aftermarket blocks are permitted. Approved aftermarket blocks include DART #31161111 or Brodix #BRS400035842 or GM #12480047 or World Products #084010.
- 13.8.5 Only stock appearing crankshafts are permitted. Lightweight cranks are not allowed. No undercut, bull nosed, gun drilled or knife edge crankshafts allowed. Balancing permitted by drilling only. Resizing journals to a maximum .030 inch under is permitted. Stroke must match block.
- 13.8.6 Lightweight, aluminum and/or fluid dampeners are not allowed. Any stock OEM steel balancer is permitted.
- 13.8.7 Must be stock appearing I-beam non-polished connecting rod. Aluminum or light weight is not allowed. GM five and seven-tenths (5.7) inches or six (6) inches rods are permitted. Only standard size rod journals and wrist pins (Chevrolet rods 2.100/.927) are permitted. Cap screw rods are permitted. Minimum weight of 530 grams is required.
- 13.8.8 Steel oil pans only with a minimum one (1) inch plug above the oil level in the side of the oil pan. If not utilizing a one (1) inch plug, oil pan may have to be removed for inspection. Wet sump oil systems only.
- 13.8.9 Only stock, unaltered two-barrel low rise cast iron intake manifolds or Approved aluminum intakes are permitted. Approved aluminum intakes are GM – Edelbrock (#2101 or #2701) or Weiand (#7547 or #7547-1); Ford – Edelbrock (#2121 or #2181 or #2665) or Weiand (#7515 or #8023 or #7516); Chrysler – Edelbrock (#2176) or Weiand (#7545 or #8022). Porting, polishing, powder coating and/or port machining is not allowed. Bowtie, aftermarket, SVO and W2, marine, VORTEC or other special production intake manifolds are not allowed. External cooler lines from back of intake to front of intake are permitted.
- 13.8.10 Cast iron stock production or unaltered aftermarket steel stock replacement heads are permitted. Porting and/or polishing is not allowed. GM cars must utilize 76cc heads (approved head numbers are 336, 339, 388, 441, 454, 487, 624, 813, 882, 991 and 993). Aftermarket head numbers are GM – EQ Part #CH350I; Dart Part #10024267 or #10024360; or World Products Part #043600 or #042670; Ford – World Products Part #53030; Chrysler – EQ Part #CH318B; or RHS/Indy Part #20300 or #20301. Heads

may be flat milled to reach the 9.5:1 compression rule. Valve size no larger than 2.02 intake and 1.60 exhaust. VORTEC heads are not allowed. Intake valves must weigh a minimum one hundred three (103) grams. Exhaust valves must weigh a minimum eighty seven (87) grams. Only stock diameter valve springs are permitted. Valve springs may not exceed a seat pressure of one hundred twenty (120) pounds. Beehive valve springs are not allowed. Only stock steel valve spring retainers permitted.

13.8.11 Screw-in studs, guide plates and poly-locks are permitted.

13.8.12 Roller cams and lifters are not allowed. Only flat tappet hydraulic camshafts with four-hundred fifty thousandths (0.450) inch maximum lift at the valve or three-hundred thousandths (0.300) inch lift at the camshaft are permitted. Full roller rocker arms are permitted. Stock-type stamped steel rocker arms or cast steel rocker arms with roller tips are permitted. Must maintain an OEM rocker arm ratio (1.5 for GM). Chryslers may utilize OEM steel shaft rockers but may not exceed one hundred twenty (120) pounds of valve spring seat pressure and must maintain OEM valve spring dimensions. Under valve cover pressurized valve train oiling systems are not allowed.

13.8.13 Mushroom lifters are not allowed. Steel stock diameter lifters only and lifter must collapse one-tenth (0.1) inch minimum.

13.8.14 Stud girdles are not allowed.

13.8.15 Any Holley 4150 Series four-barrel carburetor is permitted (see Article 7.3.4).

13.8.16 Only non-stepped headers are permitted. Must follow all header rules (See Rule 13.4).

13.8.17 Must utilize a rev limiter with a maximum setting of 6,500 RPM (See Rule 6.5).

13.8.18 Overall racecar weight must be a minimum two-thousand five hundred (2,500) pounds

13.8.19 Concept engines are subject to protests and must have "Concept" decal prominently displayed and affixed near the A pillar.

13.8.20 All USRA fuel rules apply.

ARTICLE 14: WEIGHT

14.1 The overall weight of the racecar shall be measured at the conclusion of an event with the driver in the cockpit, wearing complete racing apparel.

14.2 Overall weight of the racecar must be a minimum of two-thousand five hundred (2,500) pounds.

14.3 Ballast:

14.3.1 May not be mounted in cockpit, outside of body or hood area, or on any rotating or suspension parts. Weight must be mounted to the frame, roll cage or rearend housing only. Weight brackets for rearend housing must be made of steel.

14.3.2 Must be securely mounted, painted white and clearly marked with the car number.

14.3.3 Must be attached with at least two (2) one-half (0.5) inch bolts with a maximum of one hundred (100) pounds per mounting. Any ballast weighing twenty-five (25) pounds or less may be mounted with one (1) one-half (0.5) inch bolt.

14.3.4 May not be attached to rear bumper.

ARTICLE 15: SAFETY

15.1 It is recommended that each racecar have built-in fire extinguishing equipment but cannot be of the dry powder type (must be Halon 1211 or equivalent).

15.2 Drivers should have in their pit area as part of their equipment, at all times, a fully charged dry chemical, Halon (or its equivalent) fire extinguisher. Ten- or thirteen-pound fire extinguishers are recommended.

15.3 Driver must wear required helmet, fire suit and five-point safety harness whenever the racecar is on the racetrack. This includes during track packing, warm ups, hot laps and races.

15.4 Helmets are mandatory and must be certified SA2015 or SA2020.

15.5 Helmet must accompany driver and racecar at time of inspection.

15.6 Complete one- or two-piece fire suits of a flame retardant nature are mandatory.

15.7 Fire-resistant gloves and shoes are mandatory. Fire-resistant socks are recommended.

15.8 The use of a five- six- or seven-point driver restraint system (safety belts, sub-belt and shoulder harness) is required. Factory-type shoulder belts or straps are not allowed. The use of a seven-point driver restraint system is recommended.

15.9 Metal to metal buckles are required on shoulder and seat belts.

15.10 Shoulder harness must be mounted securely to the main roll cage.

- 15.11 Where the belt passes through the seat edges, a grommet must be installed, rolled and/or padded to prevent cutting of the belt.
- 15.12 Driver restraint system must be less than three (3) years of age past the date of manufacture. It is recommended that the driver restraint system be no more than two (2) years of age past the date of manufacture.
- 15.13 Full-size window net mounted in the left side driver's window opening is required. Window net mounts must be welded to the roll cage. All bars around the driver must have approved roll bar padding. Approved racing arm restraints are recommended.
- 15.14 Fire-resistant safety neck collars are mandatory.
- 15.15 Absolutely no plastic except from edge of firewall to body skin and inner wheel tub to body skin.

ARTICLE 16: PROTEST PROCEDURES

- 16.1 Any driver possessing a valid USRA license may have the opportunity to execute a protest on the cylinder heads and intake manifold, shocks or carburetor of another driver's racecar.
- 16.2 The first four (4) finishers in the main event must drive their racecars directly to the designated tech area at the conclusion of the main event and are subject to being protested by any other driver that finishes fifth or lower and finishes on the same lap as the winner. Any of the top four finishers that do not go to the tech area will be disqualified but are still subject to being protested.
- 16.3 Protest must be made within five (5) minutes of the completion of the main event. Protested items must be removed at the racetrack and within one (1) hour after protested driver accepts the protest.
- 16.4 Driver making a protest must drive his/her race car immediately after finish of feature, under its own power, directly to the tech area.
- 16.5 Protesting driver must present cash to official overseeing the tech area at the time that the driver declares his/her intention to protest. The cash price of a protest for cylinder heads and intake manifold shall be \$500. The cash price for a protest for carburetors shall be \$150. The cash price for a protest for shocks shall be \$100. Drivers protesting shocks may protest one or all of the shocks during a single protest. \$50 of the protest money shall go to the track officials and the remainder of the protest money shall go to the protested driver if found legal or returned to the protesting driver if items are found to be illegal. Any dispute on whether the protested part is legal or not legal will be settled by sending the part(s) to the USRA for a final decision. If the part is deemed illegal by the track officials then the driver being protested will have to pay for shipping the part to the USRA if they dispute that decision. If the part is deemed legal then the protesting driver will have to pay to have the part shipped to the USRA if they dispute the decision. Any part examined during the protesting procedure not related to the protest is still subject for inspection and may be deemed legal or illegal by the track officials.
- 16.6 Protesting driver shall select from the first four (4) finishers in the main event and must declare that choice to the official overseeing the tech area. If multiple drivers declare an intention to protest, the driver finishing farthest back in the main event will select first.
- 16.7 Driver is permitted one (1) protest per event, regardless of the outcome of that protest.
- 16.8 Only drivers, car owners and officials are permitted in the designated tech area. Any other participants associated with that racecar that enter the tech area will be subject to disqualification, fine and/or suspension.
- 16.9 Only a driver may protest, and only the protested driver or car owner may agree to accept or refuse the protest. The first statement of acceptance or rejection of the protest by the protested driver or car owner is binding.
- 16.10 Any driver or car owner refusing to accept a protest will forfeit all cash and contingency winnings for that event.
- 16.11 Any driver or car owner refusing to accept a protest forfeits his/her right to make a protest in any USRA event for a period of one (1) year from the date of refusal.
- 16.12 Any driver or car owner refusing to accept a protest will forfeit all USRA points accumulated up to, and including, the event at which the protest was made.
- 16.13 First refusal to accept a protest will result in that driver and car owner being suspended from all USRA events for thirty (30) days and until a \$1,000 fine is paid and received by the USRA. Second refusal to accept a protest will result in that driver and car owner being suspended from all USRA events for one (1) year and until a \$5,000 fine is paid and received by the USRA.
- 16.14 In the event of a dispute between driver and car owner whether to accept or refuse a protest, the decision of the driver shall overrule that of the car owner.

16.15 Any driver found to be making a protest for another person will lose all USRA points accumulated to date for the entire season, all cash and contingency winnings for that event, and will be suspended from all USRA events for thirty (30) days and until a \$1,000 fine is paid and received by the USRA.

16.16 Driver may protest a maximum of three (3) times during the calendar year.

16.17 Driver must compete in a minimum of three (3) consecutive events prior to the event at which he/she makes a protest.

16.18 The USRA reserves the right to disallow any protest at their discretion.

16.19 Drivers utilizing a provisional starting position are not allowed to make a protest in that event.

ARTICLE 17: ALTERNATIVE RULES

With prior approval from USRA, any sanctioned racetrack may utilize the option of sanctioning the B-Mod class using these Alternative Rules. This is only an option for track promoters to use and it must be advertised and posted on their website if this option is utilized. This must be decided before the season starts but may be removed at any time. This is not an option for drivers to use from race to race. All race cars utilizing these Alternative Rules may utilize a maximum three (3) inch spoiler. All race cars not utilizing these Alternative Rules are not allowed any spoiler. All other USRA rules apply.

Body: An eight (8) inch rear filler panel is required. Sail panels may be a maximum forty-three (43) inches long.

Rear suspension: A thirteen (13) inch maximum vertical rear spring centered on rearend housing with solid spring perches is required. A sixteen (16) inch minimum to nineteen (19) inch maximum rear suspension links and a twenty-three (23) inch minimum straight panhard bar mounted behind rearend housing is required. Rear shocks must be mounted behind rearend housing, Rear chains only, and if used must be mounted solid to axle housing and frame and must be loose at ride height.

Engine: Standard Engines and Crate Engines only (Concept Engines are not allowed). Stepped headers are not allowed. Maximum compression ratio of 9.0:1 with a maximum 6,600 RPM rev limiter for Standard Engines. E85 fuel is not allowed. Cold air boxes are not allowed.

Rearend: Quick change rearends are not allowed. Full spools and/or lightweight gears are not allowed.

Transmission: Clutchless transmissions are not allowed (all gears must function).

Wheels: Only three (3) and four (4) inch offset wheels are permitted. One (1) inch wheel spacers on four (4) inch offset wheels are permitted. Any other wheel spacers are not allowed.

AMENDMENTS

February 26, 2024 – Rule 1.15: Plastic valances and/or nose pieces are permitted (P.N. MD3M21100). When using a plastic nose, the upper nose filler must have a horizontal brace every twelve (12) inches to prevent the panel from becoming concaved. Concaved noses are not allowed with any material used.

##

United States Racing Association (USRA)
P.O. Box 905, Webster City, IA 50595
Office: 515-832-6000 | Fax: 515-832-7958 | usraracing.com
Darlo Mulder, Competition Director: 515-835-9946 | tech@usraracing.com

Copyright © 2023-2024 U.S. Racing, LLC. All rights reserved.